



PLAYGROUND PAINT

198-0

Yellow

Technical Data Sheet

DESCRIPTION

A water based paint for playground marking

| CHARACTERISTICS | | TECHNICAL INFORMATION | | | |
|--|---|---|--|---------|--------|
| <p>Visibility Its highly visible yellow colour creates a sharp contrast when applied on natural turf, sand, asphalt, and concrete.</p> <p>Durability This product will give a very good durability.</p> <p>Ecological This paint contains very little VOC* *(Volatile Organic Compound)</p> | Drying Time | Recoat: 30 min – 1h | To touch : 30 minutes | | |
| | | At 25° Celsius Relative humidity at 50% May differ depending on the colour | | | |
| | Surface Coverage (for 18.9L) | 960 linear feet at 4 inches wide 5 mils wet May vary depending on the field | | | |
| | | Cleaning | Lukewarm soapy water | | |
| | Dilution | None | | | |
| | Solids by Weight | 28% | | | |
| | Solids by Volume | 16% | | | |
| | VOC | < 25 g/L | | | |
| | GLOSS | 60° | N/A | | |
| | | 85° | N/A | | |
| N/A | May vary according to the texture of surface to which it will be applied on | | | | |
| TINTING BASES | | FORMATS | | COLOURS | |
| Yellow | 198-0 | 946ml | 3.78L | 18.9L | Yellow |
| | | | | X | |
| USE | | | LIMITATIONS | | |
| <ul style="list-style-type: none"> Specially manufactured for playground markings. This product may be used on natural and artificial turf, sand, asphalt and cement. | | | <ul style="list-style-type: none"> Do not use as a traffic paint. | | |

SURFACE PREPARATION

No preparation required.

SUGGESTED PRIMER

No primer required.

APPLICATION

Stir thoroughly before application. Should the paint be too thick when it's applied with a spray gun, it is recommended to dilute with a maximum of 10% water.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

The paint will then dry to a whiter finish.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

Dispose of the container in an environmentally-friendly manner.