## MF PAINT INC. MATERIAL SAFETY DATA SHEET

SECTION 1 GENERAL INFORMATION

Manufacturer: MF PAINTS inc. TDG: Not regulated Product name: Portico

1605 Dagenais West

Laval, Quebec, H7L 5A3 Product code: 230

IN CASE OF EMERGENCY, CONTACT ANTI-POISON CENTER SIMDUT: D2A, D2B

SECTION 2 HAZARDOUS INGREDIENTS

Component: % CAS No. LD 50 Species/ Route LC 50 Species/ Route

Ethylene glycol 1-2 107-21-1 8540 mg/kg (oral-rat)

7500 mg/kg (oral-mouse)

Use: Paint

10876 mg/kg (rat)

Diethylene glycol 0.5 - 1.0 112-34-5 5 660 mg/kg (Oral - rat) N/A

monobutyl ether 2 700 mg/kg (Skin – rabbit)

SECTION 3 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20½C:liquidColour: whiteSolubility in water: miscibleOdour: odourlessBoiling point: 100½CVapour pressure (mm of Hg): not applicableFreezing/ melting point: 0½CDensity (G/ML): 1.0 – 1.5Vapour density (air=1): not applicable

Volatile by weight (%): 47 - 50 Evaporation rate (n-butyl acetate=1): not applicable

SECTION 4 FIRE OR EXPLOSION RISK

Flammability: No Flash point: Closed cup: N.A. Open cup: n/a Auto-ignition temperature: N.A. Flammable limits: Lower: n/a Upper: n/a

Combustion products: carbon monoxide and other dangerous products such as aldehydes.

Extinguishing media: carbon dioxide, dry chemical, foam and water fog.

Special fire procedures: Wear full protective equipment including a self-contained breathing apparatus. Toxic gases liberated under fire conditions.

SECTION 5 REACTIVITY

Stability: Yes Reactivity: under excessive heat

Incompatibility: yes, with oxidizing agents and zinc. Do not store in galvanized recipients.

Decomposition products: When available oxygen is limited, as in a fire or when heated to very high temperatures by hot wire or plate, carbon monoxide and other hazardous

compounds such as aldehydes might be generated.

SECTION 6 TOXICOLOGICAL PROPERTIES

TOXIC EFFECTS:

Inhalation: Negligible hazard at ambient temperature. Mists may be irritating. May irritate upper respiratory tract.

skin: repeated exposure may cause slight flaking, tenderness, and softening of skin.

Ingestion: single dose or small dose: toxicity is believed to be very low. Large dose: depression of central nervous system.

Eyes: Liquid and mist may irritate the eyes. May cause slight transient (temporary) irritation.

 $\hbox{CHRONIC EFFECTS: possibility of sensitive skin.}\\$ 

TOXICOLOGICAL DATA:

Time-weighted average exposure value: no data Cancerogenicity: negative.

Mutagenicity: no data Teratogenicity: studies suggest the absence of effects.

Reproduction system effects: Results of test in animals have been negative. Other effect:

SECTION 7 PREVENTION

Gloves: wear impervious rubber gloves. Foot wear: N.A.

Equipment and clothing: impervious protective clothing Eyes protection: safety glasses

Ventilation: control airborne concentrations below the exposure guideline. Breathing protection: when respiratory equipment is required, use an NIOSH approved air

purifying

Leak or accident: Absorb with paper, sand or sawdust. Keep in a sealed container.

Waste disposal: Consult the regional office of the ministry of Environment.

Handling and storage: ventilated as required or wear an appropriate respiratory equipment. Protect your eyes. Avoid contact with eyes. Store in a well ventilated area, away

from oxyding materials.

SECTION 8 FIRST AID

Breathing: Remove to fresh air and seek medical attention if irritation occurs.

Skin contact: Wash off in flowing water or shower.

Eyes contact: Flush eyes with abundant water. If the irritation persists, contact a physician.

 $Ingestion: Do \ not \ induce \ vomiting. \ Contact \ a \ physician.$ 

SECTION 9 PREPARATION INFORMATION

We believe that the information given above is up to date at the preparation date of this toxicological index. Because the handling of this information is not upon the control of

this company, the users have the full responsibility to determine the conditions to properly and safely use this product.

Manager: Richard St-Onge Preparation date: January 2016 Phone: (450) 628-3831 Poison Centre 1-800-463-5060