MF PAINTS INC. MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION SECTION 1

Manufacturer: MF PAINTS inc.

1605 Dagenais West

Laval, Quebec, H7L 5A3

1,0-1,5

TDG: Not regulated

SIMDUT: D2A, D2B

Product name: Proline

Use: Paints

Product code: 6057

10876 mg/kg (rat)

IN CASE OF EMERGENCY, CONTACT ANTI-POISON CENTER

HAZARDOUS INGREDIENTS SECTION 2

Component: LD 50 Species/ Route LC 50 Species/ Route

8540 mg/kg (oral-rat)

7500 mg/kg (oral-mouse)

SECTION 3 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20°C: liquid Color: White Solubility in water: miscible Boiling point: 100°C Odour: odourless Vapour pressure (mm of Hg): n/a Freezing/ melting point: 0°C Density (G/ML): 1.2 - 1.4 Vapour density (air=1): n/a

Volatile by weight (%): 50-54 Evaporation rate (n-butyl acetate=1): n/a

107-21-1

SECTION 4 FIRE OR EXPLOSION RISK

Flammability: No Flash point: Closed cup: n/a Open cup: n/a Auto-ignition temperature: n/a Flammable limits: Lower: n/a Upper: n/a

Combustion products: carbon monoxide, carbon dioxide.

Extinguishing media: carbon dioxide, foam, dry chemical, alcohol foam, and water fog. Do not direct a solid stream of water or foam into hot, burning pools; this may cause frothing and increase fire intensity.

Ethylene glycol

Special fire procedures: Wear full protective equipment including a self-contained breathing apparatus. Vapours mixed with air creates an explosive mixture. Cool off exposed containers with water.

SECTION 5 REACTIVITY

Stability: yes Reactivity: under excessive heat

Incompatibility: yes, with strong acids, strong bases, strong oxidants. Reacts strongly in contact with oxidants agents or hydroxyl composants.

Decomposition products: thermic decomposition (500-600°C): carbon monoxide, carbon dioxide, acetaldehyde.

SECTION 6 TOXICOLOGICAL PROPERTIES

TOXIC EFFECTS:

Inhalation: High vapours concentrations may produce nausea, vomiting, headache, dizziness, irregular eye movements, abdominal discomfort, drowsiness, malaise, blurring of vision, lumbar pain, oliguria, uremia and central effects system, including convulsions and coma. Cardiac failure and pulmonary oedema may develop.

Ingestion: same as inhalation. Severe kidney damage follows the swallowing of large volumes of ethylene glycol. May be fatal.

Eyes: possible irritation. Excess redness and swelling of the conjuctiva may occur.

CHRONIC EFFECTS: repeated contact may cause dermatitis, conjuctiva. On animals (inhalation or ingestion): dose related increase in renal tumor incidence and hepatics.

TOXICOLOGICAL DATA:

Time-weighted average exposure value: (ppm) 50p (mg/m3) 127p Cancerogenicity: studies suggest the absence of effects.

Teratogenicity: insufficient data to evaluate. Mutagenicity: insufficient data to evaluate.

Reproduction system effects: Passes through the placental barrier in animals. Other effect: antagonism: ethanol, b6 vitamins, magnesium, pyrazole.

SECTION 7 PREVENTION

Gloves: appropriate gloves. Foot wear: n/a Equipment and clothing: protection equipment Eyes protection: glasses

Ventilation: Maintain the concentrations under the minimal exposition rate. Breathing protection: protection equipment

Leak or accident: Absorb with paper, sand or sawdust.

Waste disposal: Refer to the regional office of the environmental minister.

Handling and storage: ventilate adequately or wear an appropriate breathing apparatus Wear eye protection. Avoid contact with skin. Store in a sealed container, in a well ventilated area, away from oxidants materials.

SECTION 8 FIRST AID

Breathing: vapours incommodation, bring the person in a well ventilated area. If breathing has stopped, administer artificial respiration. Give oxygen, keep warm and call a physician.

Skin contact: Wash skin with water and soap.

Eyes contact: Flush eyes with lukewarm water . If irritation persists, consult a physician.

Ingestion: Vomit if conscient. Call a physician.

SECTION 9 PREPARATION INFORMATION

We believe that the information given above is up to date at the preparation date of this toxicological index. Because the handling of these information's are not upon the control of this company, the users have the full responsibility to determine the conditions to properly and safely use this product.

Phone: (450) 628-3831 Manager: Richard St-Onge Preparation date: March 2016