



# Latex Plus

Flat for walls & ceilings



168-0

## Technical Data Sheet

### DESCRIPTION

**LATEX Plus 168 series** is a Superior Quality decorative interior coating made of acrylic resin that produces a flat finish.

CHARACTERISTICS		TECHNICAL INFORMATION			
<p><b>Non spattering</b> Only a minimum of protection is required to protect baseboards and floors during application.</p> <p><b>Washable</b> The sheen and the colour of the <b>LATEX Plus</b> will not be affected by repeated washings with lukewarm water and mild soap solutions.</p> <p><b>Excellent hiding</b> With only 2 coats, this paint will hide most colours. To facilitate its application and for better results, use a 15mm lint free roller.</p>		<b>Drying Time</b>	Recoat: 4 – 8 hours	To touch : 1 hour	
			At 25° Celsius Relative humidity at 50% May differ depending on the colour		
		<b>Surface Coverage (for 946 ml)</b>	10.5 – 13.0m <sup>2</sup> (113 -140ft <sup>2</sup> )		
			May vary depending on the surface porosity		
		<b>Cleaning</b>	Lukewarm soapy water		
		<b>Dilution</b>	None		
		<b>Solids by Weight</b>	51%		
		<b>Solids by Volume</b>	34%		
		<b>VOC</b>	<100 g/L		
		<b>GLOSS</b>	<b>60°</b>	2.5%	
<b>85°</b>	3%				
<b>Flat</b>	May vary according to the texture of surface				
TINTING BASES		FORMATS		STANDARDS	
White	168-0	946ml	3.78L	18.9L	CGSB: Type 1GP 100, 209
P Base	168-1	X	X	X	
		X	X		
COLOURS					
A super white as well as a wide variety of off whites and pastel colours.					
Base P (max. of 2 oz of colorant/ 3,78L)					

USE	LIMITATIONS
<ul style="list-style-type: none"> <li>- For interior use</li> <li>- Can be used on unpainted and painted surfaces</li> <li>- Recommended for walls and ceilings on which a flat finish is requested</li> <li>- Can be used for residential, commercial and institutional projects</li> </ul>	<ul style="list-style-type: none"> <li>- Not for exterior use</li> <li>- Do not use on floors</li> <li>- Do not apply if temperature is below 10°C</li> <li>- Wait 15 days before the first wash</li> </ul>

### SURFACE PREPARATION

The surface must be dry and clean, with no traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

### SUGGESTED PRIMER

<b>Wood:</b>	Seal pine knots with <b>Stop Plus 298</b> prior to applying the finishing coat
<b>Drywall:</b>	Apply <b>Latex Plus 170</b> primer & sealer
<b>Masonry &amp; concrete:</b>	Apply <b>Latex Plus 170</b> primer & sealer
<b>Ferrous metal:</b>	Apply <b>ISO-RUST 4350 or 4370</b> rust-resistant primer
<b>Flat latex &amp; alkyd paint:</b>	No primer required
<b>Glossy alkyd paint:</b>	Apply an undercoat of <b>Adhero Plus 290</b>

### APPLICATION

Stir thoroughly before and during use. Apply one or two coats as required. Let dry 4 hours between coats for pale colours and 8 hours for dark colours. A 15mm lint free roller or a quality bristle brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with soapy lukewarm water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul>

***Dispose of the container in an environmentally-friendly manner.***