

## PLAYGROUND PAINT

197-0

Blue

# **Technical Data Sheet**

### DESCRIPTION

A water based paint for playground marking

| CHARACTERISTICS  | TECHNICAL INFORMATION              |   |                       |
|--|------------------------------------|---|-----------------------|
| Visibility Its highly visible blue colour creates a sharp contrast when applied on natural turf, sand, asphalt, and concrete.                          | Drying Time                        | Recoat: 30 min – 1h   | To touch : 30 minutes |
| Durability Specially formulated to provide a good durability.  |                                    | At 25° Celsius<br>Relative humidity at 50%<br>May differ depending on the colour  |                       |
|  | Surface<br>Coverage<br>(for 18.9L) | 960 linear feet at 4 inches wide<br>5 mils wet<br>May vary depending on the field |                       |
|  | Cleaning                           | Lukewarm soapy water  |                       |
|  | Dilution                           | None  |                       |
|  | Solids by<br>Weight                | 26%   |                       |
|  | Solids by<br>Volume                | 15%   |                       |
|  | voc                                | < 100 g/L   |                       |
|  | GLOSS                              | <b>60°</b>   N/A   <b>85°</b>   N/A   |                       |
|  | N/A                                | May vary according surface to which it w  |                       |
| TINTING BASES FORMATS  | COLOURS                            |   |                       |
| Blue 197-0 946ml 3.78L 18.9L X   | Blue                               |   |                       |
|  |                                    |   |                       |
| USE  | LIMITATIONS                        |   |                       |
| <ul> <li>Specially manufactured for playground markings. This product may be used on natural and artificial turf, sand, asphalt and cement.</li> </ul> | - Do not use as a traffic paint.   |   |                       |

#### SURFACE PREPARATION

No preparation required.

#### SUGGESTED PRIMER

No primer required.

#### **APPLICATION**

Stir thoroughly before application. Should the paint be too thick when it's applied with a spray gun, it is recommended to dilute with a maximum of 10% water.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

The paint will then dry to a whiter finish.

| WARRANTY  | CAUTION                                 |  |  |
|---|---|--|--|
| This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection. | -Keep in a dry area between 10° C-30° C |  |  |

Dispose of the container in an environmentally-friendly manner.

MF Paints inc., 1605 Dagenais BLVD. West Laval, Quebec, H7L 5A3 Customer Service 1-800-363-8034