



# BLOCK FILLER

206-0

For cement blocks

## Technical Data Sheet

### DESCRIPTION

**BLOCK FILLER 206** series is an emulsified latex based primer sealer (block filler) for concrete blocks.

| CHARACTERISTICS  |       | TECHNICAL INFORMATION   |                  |
|--|-------|---|------------------|
| <p><b>Block filler</b><br/>Its strong consistency allows irregular surface cavities to be filled and sealed.</p> <p><b>Excellent sealer</b><br/>Seals the surface in order to obtain an even finish with the topcoat of paint.</p> <p><b>Ecological</b><br/>This paint has a low VOC* content (&lt; 50 g/L)<br/>*(Volatile Organic Compound)</p> |       | <p><b>Drying Time</b></p> <p>Recoat: 2-4 hours      To touch : 1 hour</p> <p>At 25° Celsius<br/>Relative humidity at 50%<br/>May differ depending on the colour</p> |                  |
|  |       | <p><b>Surface Coverage (for 946 ml)</b></p> <p>4 – 6 m<sup>2</sup> (43 – 65 ft<sup>2</sup>)<br/>May vary depending on the surface porosity</p>                      |                  |
|  |       | <p><b>Cleaning</b></p> <p>Lukewarm soapy water</p>  |                  |
|  |       | <p><b>Dilution</b></p> <p>None</p>  |                  |
|  |       | <p><b>Solids by Weight</b></p> <p>65-70 %</p>   |                  |
|  |       | <p><b>Solids by Volume</b></p> <p>50-53 %</p>   |                  |
|  |       | <p><b>VOC</b></p> <p>&lt;100 g/L (type MPI E range=3)</p>   |                  |
|  |       | <p><b>GLOSS</b></p> <p><b>60°</b>      2.5%</p> <p><b>85°</b>      4.5%</p>   |                  |
|  |       | <p><b>FLAT</b></p> <p>May vary according to the texture of surface to which it will be applied on</p>   |                  |
| TINTING BASES  |       | FORMATS   |                  |
| White  | 206-0 | 946ml   | 3.78L 18.9L<br>X |
| COLOURS  |       | STANDARDS   |                  |
| White  |       | <p><b>CGSB:</b> Type 1GP 188</p> <p><b>CFIA:</b> Product approved<br/>(Canadian Food Inspection Agency)</p>   |                  |

| USE   | LIMITATIONS   |
|---|---|
| <ul style="list-style-type: none"> <li>- For interior use. If used outdoors it must be covered with the proper topcoat.</li> <li>- Recommended for concrete block walls</li> <li>- Suitable for residential, commercial and institutional projects</li> </ul> | <ul style="list-style-type: none"> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply on floors</li> </ul> |

### SURFACE PREPARATION

The surface must be dry and clean, without traces of dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

### APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 2 hours or more between coats. In order to properly seal the surface, the use of a 15mm lint free roller or a quality polyester/nylon brush are recommended. For a spray application, dilute with a maximum of 10% water. If sprayed, roll over with a wet roller before the surface dries to enhance penetration of the surface cavities. Clean brushes and rollers with soapy lukewarm water.

**Note: Use an airless pump with a minimum 0.021inch opening. Remove the pump and the gun filters**

| WARRANTY   | CAUTION  |
|--|--|
| <p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p> | <ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul> |

***Dispose of the container in an environmentally-friendly manner.***