



# PREMIUM

## Primer Sealer



# 370-0

### Technical Data Sheet

#### DESCRIPTION

**Premium 370** is latex acrylic based primer sealer. It is formulated to seal new drywall.

CHARACTERISTICS		TECHNICAL INFORMATION	
<p><b>Sealant</b> This product seals drywall.</p> <p><b>Sanding</b> Easy to sand after 3 hours without overloading the sand paper.</p> <p><b>Fast drying</b> Can be recoated after only 3 hours.</p>	<b>Drying Time</b>	Recoat: min 3 hours	To touch : 1 hour
		At 25° Celsius Relative humidity at 50% May differ depending on the colour	
	<b>Surface Coverage (for 946 ml)</b>	8.2 - 10.5 m <sup>2</sup> (88 – 113 ft <sup>2</sup> )	
		May vary depending on the surface porosity	
	<b>Cleaning</b>	Lukewarm soapy water	
	<b>Dilution</b>	None	
	<b>Solids by Weight</b>	53%	
	<b>Solids by Volume</b>	34%	
	<b>VOC</b>	<50 g/L	
	<b>GLOSS</b>	60°	N/A
85°		N/A	
May vary according to the texture of surface to which it will be applied on			
TINTING BASES		FORMATS	
White	370-0	946ml	3.78L 18.9L
			X X
COLOURS		STANDARDS	
White		CGSB: Type 1GP 119	

USE	LIMITATIONS
<ul style="list-style-type: none"> <li>- For interior use</li> <li>- Can be used on new surfaces such as; drywall, concrete and wood.</li> <li>- Can be used for residential and institutional projects.</li> </ul>	<ul style="list-style-type: none"> <li>- Do not apply outdoors</li> <li>- Do not apply on floors</li> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply over alkyd based paint</li> <li>- Do not apply under Pearl or higher gloss surfaces</li> <li>- Can crack if overloaded in corners</li> </ul>

### SURFACE PREPARATION

The surface must be dry and clean, with no traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

### APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 3 hours or more. A 15mm lint free roller or a quality bristle brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with soapy lukewarm water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul>

**Dispose of the container in an environmentally-friendly manner.**