



Technical Data Sheet

Proline ECO

**Ceiling flat
Self-Priming
Zero VOC**



7050



DESCRIPTION

PROLINE ECO zero VOC 7050 ceiling flat finish does not contain any volatile organic compounds that can contribute to air pollution.

CHARACTERISTICS		TECHNICAL INFORMATION				
<p>Zero VOC This paint is ideal for LEED certified projects as well as for any other project requiring a zero VOC paint</p> <p>Self-Priming Allows to paint and prime new drywall at once.</p> <p>Non spattering Only a minimum of protection is required to protect baseboards and floors during application.</p> <p>Quick drying & low odor Can be recoated after only 4 hours.</p>		Drying Time	Recoat: 4 hours	To touch : 1 hour		
			At 25° Celsius Relative humidity at 50% May differ depending on the colour			
		Surface Coverage (for 946 ml)	9.3 – 11.7 m ² (100 -125ft ²)		May vary depending on the surface porosity	
			Cleaning	Lukewarm soapy water		
		Dilution	None			
		Solids by Weight	47%			
		Solids by Volume	32%			
		VOC	Zero			
		GLOSS	60°	2.2%		
			85°	2.2%		
Ceiling flat	May vary according to the texture of surface to which it will be applied on					
TINTING BASES		FORMATS		STANDARDS		
Neutral White 7050-8		946ml	3.78L	18.9L	<p>MPI: Certified category #143, GPS-1, GPS-2 (Master Paint Institute)</p> <p>Green Seal: Type GS-11</p>	
			X	X		
COLOURS		<p>CGSB: Type 1GP 100</p> <p>CFIA: Product approved (Canadian Food Inspection Agency)</p>				
A neutral white to make pastel colours.						
Neutral White (max. of 2 oz of colorant/ 3,78L)						

USE	LIMITATIONS
<ul style="list-style-type: none"> - For interior use - Can be used on new or painted surfaces - Recommended for ceilings on which a flat finish is required - Suitable for residential, commercial or institutional projects 	<ul style="list-style-type: none"> - Do not apply if temperature is below 10°C - Not for exterior use - Do not apply on floors - Wait 30 days before the first wash - Do not scrub with recurring or ammonia based products

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

SUGGESTED PRIMER

- Wood:** Seal pine knots with **Stop Plus 298** prior to applying the finishing coat
- Drywall:** Apply directly onto the drywall, 2 coats are necessary.
- Masonry:** Seal the surface with one coat of **Proline ECO 7070** primer & sealer prior to top coat.
- Ferrous metal:** Apply **ISO-RUST 4350 or 4370** rust-resistant primer
- Flat latex & alkyd paint:** No primer required
- Glossy alkyd paint:** Apply an undercoat of **Proline ECO 7090**

APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 4 hours between each coat. A 15mm lint free roller or a quality nylon-polyester brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with lukewarm soapy water.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

Dispose of the container in an environmentally-friendly manner.