



Sélection 5365-C SERIES

Satin
Latex acrylic

TECHNICAL DATA SHEET

DESCRIPTION

Selection 5365 satin finish is a latex acrylic paint for indoor use. It is easy to apply, without spattering and dries quickly. **Selection 5365** is designed for residential and maintenance projects.

USE	LIMITATIONS
This paint is applicable on interior surfaces. Selection 5365 must be applied to surfaces that have been well prepared and properly primed. This paint is suitable for new or used surfaces. It is recommended for walls.	Avoid application in all temperatures under 10°C Do not use on flooring Do not mix with other paints Do not apply to places subject to frequent cleaning Do not apply in high traffic areas.

CHARACTERISTICS

- Offers excellent leveling and a soft, smooth finish.
- Exceeds Canadian standards due to its low VOC.

TINTING BASES

		946 ml	3,78 L	18,9 L	
5365-0	White		X	X	
5365-1	P Base		X	X	max. of 2oz of colorant / 3,78 L
5365-2	M Base		X		max. of 5oz of colorant / 3,78 L
5365-4	D Base		X		max. of 8oz of colorant / 3,78 L
5365-5	A Base		X		max. of 12oz of colorant / 3,78 L

TECHNICAL INFORMATION

DRYING TIME	Recoat:	To touch:
	4-8 hours	1 hour
At 25° Celsius. Relative humidity at 50%. May differ depending on the colour		
SURFACE COVERAGE (for 3.78 L)	37 - 44 m ² (400 - 475 ft ²) May vary depending on the surface	
Recommended film thickness	Wet : 3,4 - 4.0 mils Dry : 1.16 - 1.37 mils	
Cleaning	Lukewarm soapy water	
Resin	Latex acrylic	
Thinner	Water	
Inflammability	N/A	
Flash point	N/A	
% of solids by weight	47%	
% of solids by volume	34%	
VOC	32 g/L	
GLOSS	60° 3-5%	
Satin	85° 12-18%	
	The value is measured based on the white. The value may vary according to the chosen colour.	

SURFACE PREPARATION

MF Paints inc., 1605 Dagenais blvd. West
Laval, Quebec (H7L 5A3)
Customer support : 1-800-363-8034

RECOMMENDED PRIMER

<p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p>Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> <p>Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound must be used to fill holes and uneven surfaces. Sand with a #100 grit sandpaper.</p> <p>New drywall: In order to avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.</p> <p>Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Remove all traces of oxidation (rust), then clean with Metal Plus 467, metal conditioner.</p> <p>Wood: The surface must be sanded with a #80 or #100 grit sandpaper to smoothen the surface.</p>	<p>Drywall: Use primer; Selection 5365 or Proline 6070.</p> <p>Concrete blocks/rough brick: Apply Proline 6006 block filler to level the surface or apply Selection 5365 directly.</p> <p>New Concrete: Apply Selection 5365 directly onto the surface.</p> <p>New wood: Use the Portico 270.</p> <p>Pine knots: Seal the pine knots with the Stop Plus 298.</p> <p>Red cedar and redwood: Apply one to two coats of Block Plus 296 alkyd based.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Apply a coat of Adhero Plus 290 or Adhero Hybrid 297.</p> <p>Latex paint: No primer is required.</p> <p>Alkyd paint: Apply an undercoat of Adhero Plus 297.</p> <p>Dark colours: Some dark colours may require the application of a dark tinted primer in order to improve opacity. Use Proline products 6070-2 and 6070-4 or Adhero Plus 290-2 and 290-4, available in more than 30 colours.</p> <p><i>If the surface to be primed is not mentioned, please contact an MF Paints distributor for further recommendations.</i></p>
<p>APPLICATION</p>	<p>MAINTENANCE</p>
<p>This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colours and 8 hours for dark colours. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.</p> <p>For spray application : Dilute with a maximum of 10% water.</p> <p>Pressure : 2000 to 2500 lb/in²*</p> <p>Nozzle : 0.015 – 0.019*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p>	<p>Allow a 30 day drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface using a light, circular motion.</p> <p>STORAGE</p> <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p>
<p>WARRANTY</p>	<p>CAUTION</p>
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> • Keep away from children's reach • Keep lid closed when not in use • Avoid freezing

" Contact your municipality to dispose of the container in an environmentally-friendly manner "