



LATEX Plus

C168 SERIES

Walls and Ceilings Flat
Latex acrylic

TECHNICAL DATA SHEET

DESCRIPTION

Our **Latex Plus 168** flat finish is a latex acrylic paint of superior quality for indoor use. It is easy to apply, without spattering and dries quickly. **Latex Plus 168** can be used for commercial and residential projects.

USE	LIMITATIONS
This paint is applicable on interior surfaces. Latex Plus 168 must be applied to surfaces that have been well prepared and properly primed. It will hide most existing colours with only two coats. It is recommended for walls and ceilings. Its flat finish allows to hide the surface imperfections.	Avoid application in all temperatures under 10°C Do not apply outside Do not use on flooring Do not mix with other paints Do not apply to places subject to frequent cleaning Do not apply in high traffic areas

CHARACTERISTICS	TECHNICAL INFORMATION					
<ul style="list-style-type: none"> During the work, minimal protection is required for baseboards and flooring. On a well prepared and primed surface of similar colour, two coats of Latex Plus 168 is enough. The uniformity of the film results in better opacity and a smooth finish for superior leveling. 	DRYING TIME <table border="1"> <tr> <td>Recoat:</td> <td>To touch:</td> </tr> <tr> <td>4-8 hours</td> <td>30 minutes</td> </tr> </table>	Recoat:	To touch:	4-8 hours	30 minutes	
Recoat:		To touch:				
4-8 hours	30 minutes					
	At 25° Celsius Relative humidity at 50% May differ depending on the colour					
	SURFACE COVERAGE (3.78 L)	33 - 42 m ² (350 - 450 ft ²) May vary depending on the surface porosity				
	Recommended film thickness	Wet : 3,6 - 4,6 mils Dry : 1,20 - 1,54 mils				
	Cleaning	Lukewarm soapy water				
	Resin	Latex acrylic				
	Thinner	Water				
	Inflammability	N/A				
	Base	1				
	% of solids by weight	49.3%				
	% of solids by volume	32.7%				
	VOC	39 g/L				
	GLOSS Flat	60° 2,0 - 3,0% 85° 3,0- 5,0% The value is measured based on the base P. The value may vary according to the chosen				
TINTING BASES	FORMAT					
	946 ml, 3,78 L, 18,9 L					
168-1 P Base	X	max. of 2 oz of colorant / 3,78 L				

SURFACE PREPARATION	RECOMMENDED PRIMER	
<p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p>Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> <p>Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth.</p> <p>A repair compound must be used to fill holes and uneven surfaces. Sand with a #100 grit sandpaper.</p> <p>New drywall : In order to avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.</p> <p>Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Remove all traces of oxidation (rust), then clean with Metal Plus 467, metal conditioner.</p> <p>Wood: The surface must be sanded with a #80 or #100 grit sandpaper to smoothen the surface.</p>	<p>Drywall: Use primer; Latex Plus 170.</p> <p>Concrete blocks/rough brick: Apply the Proline 6006 block filler to level the surface or apply two coats of Latex Plus 168 directly.</p> <p>New Concrete: Apply Latex Plus 168 directly onto the surface.</p> <p>New wood: Use the Portico 270.</p> <p>Pine knots: Seal the pine knots with the Stop Plus 298.</p> <p>Red cedar and redwood: Apply one to two coats of Block Plus 296, alkyd based.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Apply a coat of Adhero Plus 290.</p> <p>Latex paint: No primer is required.</p> <p>Alkyd paint: Apply an undercoat of Adhero Hybride 297/290.</p> <p><i>If the surface to be primed is not mentioned, please contact an MF Paints distributor for further recommendations.</i></p>	
APPLICATION	MAINTENANCE	
<p>This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.</p> <p>For spray application : Dilute with a maximum of 10% water.</p> <p>Pressure : 2000 to 2500 lb/in²*</p> <p>Nozzle : 0.015 – 0.019*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p>	<p>Allow a 30 day drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface using a light, circular motion.</p> <th data-bbox="833 1339 1490 1373">STORAGE</th> <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p>	STORAGE
WARRANTY	CAUTION	
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> • Keep away from children's reach • Keep lid closed when not in use • Avoid freezing 	

" Contact your municipality to dispose of the container in an environmentally-friendly manner "