



Selection

C5365 SERIES

TECHNICAL DATA SHEET

INTERIOR

SATIN
LATEX ACRYLIC

DESCRIPTION

Selection 5365 satin finish is a latex acrylic paint for indoor use. It is easy to apply, without spattering and dries quickly. Selection 5365 is designed for residential and maintenance projects.

USE

This paint is applicable on interior surfaces. Selection 5365 must be applied to surfaces that have been well prepared and properly primed. This paint is suitable for new or used surfaces. It is recommended for walls.

CHARACTERISTICS

- Offers excellent leveling and a soft, smooth finish.
- Exceeds Canadian standards due to its low VOC

LIMITATIONS

- Avoid application in all temperatures under 10°C
- Do not use on flooring
- Do not mix with other paints
- Do not apply to surfaces subject to frequent cleaning
- Do not apply in high traffic areas.

TECHNICAL DATA

Resin	Latex Acrylic		
Thinner	Water		
Cleaning	Lukewarm soapy water		
Flash Point	N/A		
Inflammability	N/A		
Solids by weight	48	%	
Solids by volume	35	%	
VOC	<50	g/l	
Gloss	60°	3-8	%
Sheen	85°	20-30	%

The value is measured based on the P base. The value may vary according to the chosen colour.

APPLICATION DATA

Surface Coverage		37-44 m ² (400-475) sqft	3,78 L
May vary depending on the surface porosity			
Recommended Film	Wet	3,4-4,0	mils
	Dry	1,16-1,37	mils
Drying Time	To touch	1	hour
	Recoat	4-8	hours
At 25° Celsius - Relative humidity at 50% - May differ depending on the colour			
Application	Brush	√	
	Roller	15	mm
	Spray Airless (Nozzle(0,015-0,019)*)	2000-2500	lb/sqin
*This data may vary depending on the equipment of a manufacturer			
Storage	Temperature between	10 and 30	°C
Tinting Bases		Format	Maximum Quantity of colorant
Bases	946ML	3,78L	18,9L
5365-0 White		√	√
5365-1 P Base		√	√
5365-2 M Base		√	
5365-4 D Base		√	
5365-5 Base A		√	



SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound must be used to fill holes and uneven surfaces. Sand with a #100 grit sandpaper.

New drywall: To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.

Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.

Aluminum, galvanized metal, and interior ferrous metal: Remove all traces of oxidation (rust), then clean with Metal Plus 467, metal conditioner or an appropriate conditioner.

Wood: The surface must be sanded with a #80 or #100 grit sandpaper to smoothen the surface.

RECOMMENDED PRIMERS

Drywall: Use primer; Selection 5371 or Latex Plus 170 or Proline 7070..

Concrete blocks/rough brick: Apply Proline 6006 block filler to level the surface or apply Selection 5365 directly.

New Concrete: Apply Selection 5365 directly onto the surface.

New wood: Use the Portico C270.

Pine knots: Seal the pine knots with the Stop Plus 298.

Red cedar and redwood: Apply one to two coats of Block Plus 296 alkyd based.

Aluminum, galvanized metal, and interior ferrous metal: Apply a coat of Adhero Plus 290.

Latex paint: No primer is required.

Alkyd paint: Apply an undercoat of Adhero Plus 290*.

Dark colours: Some dark colours may require the application of a dark tinted primer to improve opacity. Use Proline products 6070-2 and 6070-4 or Adhero Plus C290-2 and C290-4, available in more than 30 colours.

If the surface to be primed is not mentioned, please contact an MF Paints distributor for further recommendations.

*See limitations for Adhero Plus 290.

APPLICATION

This product is ready to use and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow 3 hours drying time between coats for light colors and 8 hours for dark colors. To properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. Clean rollers and brushes with warm soapy water after using them.

For spray application: Maybe diluted with a maximum of 10% water.

Pressure: 2000 to 2500 lb/sqin**

Nozzle: 0.015 – 0.019**

**This data may vary depending on the brand of the equipment manufacturer.

MAINTENANCE

The paint requires a minimum drying time of 30 days before proceeding with a first cleaning. It is not designed for a high frequency of cleaning. Use only mild cleaners, without abrasives, and a soft cloth. Clean the surface with a light and circular movement.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing