



Selection

C5371

TECHNICAL DATA SHEET

INTERIOR

LATEX ACRYLIC
PRIMER SEALER**DESCRIPTION**

Selection 5371 is a latex acrylic primer sealer for indoor use. It is easy to apply, without spattering and dries quickly. Selection 5371 is designed for residential and maintenance projects.

USE

The primer is applicable on interior surfaces. Selection 5371 must be applied to surfaces that have been well prepared. It is suitable for new or used latex surfaces.

CHARACTERISTICS

- Offers excellent leveling and a soft, smooth finish.
- Exceeds Canadian standards due to its low VOC

LIMITATIONS

- Avoid application in all temperatures under 10°C
- Do not use on flooring
- Do not mix with other paints
- Do not apply to surfaces subject to high humidity
- Do not apply in high traffic areas.

TECHNICAL DATA

Resin	Latex Acrylic		
Thinner	Water		
Cleaning	Lukewarm soapy water		
Flash Point	N/A		
Inflammability	N/A		
Solids by weight	50	%	
Solids by volume	32	%	
VOC	<50	g/l	
Gloss	60°	N/A	%
Sheen	85°	N/A	%

APPLICATION DATA

Surface Coverage		35-42 m ²	
May vary depending on the surface porosity		(375-450) sqft	3,78 L
Recommended Film	Wet	3,6-4,3	mils
Thickness	Dry	1,14-1,37	mils
Drying Time	To touch	30	min
	Recoat	4	hours
At 25° Celsius - Relative humidity at 50% - May differ depending on the colour			
Application	Brush	√	
	Roller	15	mm
	Spray Airless (Nozzle 0,015-0,019)*	2000-2500	lb/sqin
*This data may vary depending on the equipment of a manufacturer			
Storage	Temperature between	10 and 30	°C
Tinting Bases		Format	Maximum Quantity of colorant
Base	946ML	3,78L	18,9L
5371-0 White		√	√
			N/A



Selection

C5371

TECHNICAL DATA SHEET

INTERIOR

LATEX ACRYLIC
PRIMER SEALER

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound must be used to fill holes and uneven surfaces. Sand with a #100 grit sandpaper.

New drywall: To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.

Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.

Aluminum, galvanized metal, and interior ferrous metal: Remove all traces of oxidation (rust), then clean with Metal Plus 467, metal conditioner or an appropriate conditioner.

Wood: The surface must be sanded with a #80 or #100 grit sandpaper to smoothen the surface.

APPLICATION

This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat. To properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.

For spray application: Dilute with a maximum of 10% water.

Pressure: 2000 to 2500 lb/in²*

Nozzle: 0.015 – 0.019*

*This data may vary depending on the brand of the equipment manufacturer.

MAINTENANCE

Must be topcoated.

STORAGE

Store the paint in a dry area and maintain temperature between 10°C and 30°C

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER