



TECHNICAL DATA SHEET



INTERIOR

C7070

LATEX ACRYLIC PRIMER SEALER

DESCRIPTION

Proline Eco 7070 is an acrylic latex primer sealer for indoor use. It is easy to apply and dries quickly. It is formulated to seal new drywall. It was developed to answer the needs of professional painters. Proline Eco 7070 can be used for commercial, industrial and residential projects.

USE

This primer sealer is applicable on interior surfaces. It seals and hides repairs to obtain a uniform gloss once the topcoat is applied. Proline Eco 7070 is recommended for new surfaces such as drywall, concrete, and wood.

CHARACTERISTICS

- It is ideal for LEED projects or any other projects
- Approved MPI category #149
- It seals drywall and joint compound.
- Proline Eco 7070 can easily be sanded after 3 hours drying time without overloading the sandpaper.
- It provides good hiding.

LIMITATIONS

- Avoid application in all temperatures under 10°C
- Not for exterior use
- Do not use on flooring
- Do not apply on alkyd paint
- Do not mix with other paint

TECHNICAL DATA

Resin	Latex Acrylic		
Thinner	Water		
Cleaning	Lukewarm soapy water		
Flash Point	N/A		
Inflammability	N/A		
Solids by weight	56,2	%	
Solids by volume	40,8	%	
VOC	<30	g/l	
Gloss	60°	N/A	%
Sheen	85°	N/A	%
The value is measured based on the P base. The value may vary according to the chosen colour.			
Standards	MPI	Category #149, GPS-1, GPS-2	
	ONGC	Type 1GP 119	
	CFIA	Product approved	
	LEED	Eligible for LEED® v4	
		CDPH Emissions Certified	

APPLICATION DATA

Surface Coverage		37-46 m ²	
May vary depending on the surface porosity		(400-500) sqft	3,78 L
Recommended Film	Wet	3,2-4,0	mils
Thickness	Dry	1,29-1,62	mils
Drying Time	To touch	30	min
	Recoat	4	hours
At 25° Celsius - Relative humidity at 50% - May differ depending on the colour			
Application	Brush	√	
	Roller	15	mm
	Spray Airless (Nozzle(0,015-0,019)*)	2000-2500	lb/sqin
*This data may vary depending on the equipment of a manufacturer			
Storage	Temperature between	10 and 30	°C
Tinting Bases		Format	Maximum Quantity of colorant
Base	946ML	3,78L	18,9L
7070-0 White		√	N/A



TECHNICAL DATA SHEET



INTERIOR

C7070

LATEX ACRYLIC PRIMER SEALER

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound should be used to fill holes and uneven surfaces. Sand with a grit #100 sandpaper.

New drywall: To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.

Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.

Wood: The surface must be sanded with a grit #80 or #100 sandpaper to smoothen the surface. Cover pine knots with Stop Plus 298 to slow down the bleeding. For redwood or red cedar use Block Plus 296.

APPLICATION

This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat. To properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.

For spray application: Dilute with a maximum of 10% water.

Pressure: 2000 to 2500 lb/in²*

Nozzle: 0.015 – 0.019*

**This data may vary depending on the brand of the equipment manufacturer.*

MAINTENANCE

Must be topcoated

STORAGE

Store the paint in a dry area and maintain temperature between 10°C and 30°C

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER