



PLAYGROUND PAINT

196-0

White

Technical Data Sheet

DESCRIPTION

A latex water based white paint for playground marking

CHARACTERISTICS		TECHNICAL INFORMATION		
<p>Visibility Its highly visible white colour creates a sharp contrast when applied on natural turf, sand, asphalt, and concrete.</p> <p>Durability Offers superior durability then a standard quality product</p> <p>Ecological This paint contains very little VOC* *(Volatile Organic Compound)</p>	Drying Time	Recoat: 4-6 hours	To touch : 30 to 40 minutes	
		At 25° Celsius Relative humidity at 50% May differ depending on the colour		
	Surface Coverage (for 18.9L)	960 linear feet at 4 inches wide 5 mils wet May vary depending on the field		
		Cleaning	Lukewarm soapy water	
	Dilution	None		
	Solids by Weight	45% ± 2%		
	Solids by Volume	30% ± 2%		
	VOC	< 25 g/L		
	GLOSS	60°	N/A	
		85°	N/A	
N/A	May vary according to the texture of surface to which it will be applied on			
TINTING BASES		FORMATS		
White	196-0	946ml	3.78L 18.9L	
			X	
		COLOURS		
		White		
USE		LIMITATIONS		
<p>- Specially manufactured for playground markings. This product may be used on natural and artificial turf, sand, asphalt and cement.</p>		<p>- Apply when the ambient temperature is between 10 ° C and 30 ° C</p> <p>- Do not apply when the humidity is very high (80% or more)</p> <p>- Do not use for road signs</p>		

SURFACE PREPARATION

No preparation required.

SUGGESTED PRIMER

No primer required.

APPLICATION

Stir thoroughly before application. Upon request, the viscosity can be adjusted in advance.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

Damper the grass, the colour pigments will more likely settle to be lighter following its application. The paint will then dry to a whiter finish.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

Dispose of the container in an environmentally-friendly manner.