



PLAYGROUND PAINT

199-0

White

Technical Data Sheet

DESCRIPTION

A water based paint for playground marking

CHARACTERISTICS		TECHNICAL INFORMATION			
<p>Visibility Its highly visible white colour creates a sharp contrast when applied on natural turf, sand, asphalt, and concrete.</p> <p>Durability This product is adequate for several events and will naturally disintegrate when rained on or following a prolonged exposure to sun.</p> <p>Ecological This paint contains very little VOC* *(Volatile Organic Compound)</p>		Drying Time	Recoat: 30 min – 1h	To touch : 30 minutes	
			At 25° Celsius Relative humidity at 50% May differ depending on the colour		
		Surface Coverage (for 18.9L)	960 linear feet at 4 inches wide 5 mils wet May vary depending on the field		
			Cleaning	Lukewarm soapy water	
		Dilution	None		
		Solids by Weight	25%		
		Solids by Volume	13.5%		
		VOC	< 25 g/L		
		GLOSS	60°	N/A	
			85°	N/A	
N/A	May vary according to the texture of surface to which it will be applied on				
TINTING BASES		FORMATS		COLOURS	
White	199-0	946ml	3.78L	18.9L	White
				X	

USE	LIMITATIONS
<ul style="list-style-type: none"> - Specially manufactured for playground markings. This product may be used on natural and artificial turf, sand, asphalt and cement. 	<ul style="list-style-type: none"> - Do not use as a traffic paint.

SURFACE PREPARATION

No preparation required.

SUGGESTED PRIMER

No primer required.

APPLICATION

Stir thoroughly before application. Upon request, the viscosity can be adjusted in advance.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

Damper the grass, the colour pigments will more likely settle to be lighter following its application. The paint will then dry to a whiter finish.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

Dispose of the container in an environmentally-friendly manner.