




Technical Data Sheet

# Paint for Calcimine surfaces

Alkyd  
Flat finish  
Interior/ Exterior



1320-0

## DESCRIPTION

1320 is a high-quality alkyd based paint, specially made to seal and adhere to calcimine surfaces. For interior and exterior use.

## CHARACTERISTICS

This paint's excellent adhesion properties allow for it to be easily applied on glossy or calcimine surfaces.

Thanks to its concealing power, this paint hides coloured surfaces and water rings.

## TECHNICAL INFORMATION

<b>Drying Time</b>	Recoat: 12-24 hours	To touch: 8 hours
	At 25° Celsius Relative humidity at 50% May differ depending on the colour	
<b>Surface Coverage (for 946 ml)</b>	9.3 – 10.5 m <sup>2</sup> (100 – 113 ft <sup>2</sup> ) May vary depending on the surface porosity	
<b>Cleaning</b>	Mineral spirit (MF-SOL 450)	
<b>Dilution</b>	None	
<b>Solids by Weight</b>	72%	
<b>Solids by Volume</b>	51%	
<b>Flash Point</b>	42°C	
<b>VOC</b>	<400 g/L	
<b>GLOSS</b>	60°	2.5%
	85°	3%
<b>Semi-Gloss</b>	May vary according to the texture of surface	

## TINTING BASES

White	1320-0
-------	--------

## FORMATS

946ml	3.78L	18.9L
X	X	X

## STANDARDS

## COLOURS

Super white

USE	LIMITATIONS
<ul style="list-style-type: none"> <li>- For interior or exterior use</li> <li>- Can be used on bare and painted surfaces</li> <li>- Recommended for calcimine surfaces on which a flat finish is required</li> <li>- Outdoors, it can be used on sidings, fences, terraces, patios and wood furniture</li> </ul>	<ul style="list-style-type: none"> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply under direct sunlight</li> </ul>

### SURFACE PREPARATION

The surface must be dry and clean, without traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting. If the calcimine product is textured, you must scrub the surface with a broom in order to remove the fragile elements.

#### **Mildew & new surfaces**

On new or treated wood, having been exposed to inclement weather, it is highly recommended to neutralise all mildew, visible or not, in order to avoid peeling. Use a mix of 3 parts water for 1 part bleach, let this work for 20 minutes, then rinse and allow the wood to dry for at least 24 hours before painting. Once the surface is dry, sand the horizontal surface entirely with a n°80 sand paper in order to open the wood fibers and enhance the adhesion. Use a n°120 sand paper for vertical surfaces. Should a pressure wash be required, it must be done prior to sanding.

### SUGGESTED PRIMER

No required primer for this product

### APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 12 hours between each coat. A 10mm anti-felting roller or a quality bristle brush is recommended to enhance its application. For a spray application, dilute with a maximum of 10% mineral essence MF-SOL 450. Clean brushes and rollers with mineral essence.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul>

**KEEP AWAY FROM FLAMES OR SPARKS**

***Dispose of the container in an environmentally-friendly manner.***