



Technical Data Sheet

Latex Plus

Flat for walls & ceilings



168-0

DESCRIPTION

LATEX Plus 168 series is a Superior Quality decorative interior coating made of acrylic resin that produces a flat finish.

CHARACTERISTICS

Non spattering

Only a minimum of protection is required to protect baseboards and floors during application.

Washable

The sheen and the colour of the LATEX Plus will not be affected by repeated washings with lukewarm water and mild soap solutions.

Excellent hiding

With only 2 coats, this paint will hide most colours. To facilitate its application and for better results, use a 15mm lint free roller.

TECHNICAL INFORMATION

Drying Time	Recoat: 4 – 8 hours	To touch : 1 hour
	At 25° Celsius Relative humidity at 50% May differ depending on the colour	
Surface Coverage (for 946 ml)	10.5 – 13.0m ² (113 -140ft ²) May vary depending on the surface porosity	
Cleaning	Lukewarm soapy water	
Dilution	None	
Solids by Weight	51%	
Solids by Volume	34%	
VOC	<100 g/L	
GLOSS	60°	2.5%
	85°	3%
Flat	May vary according to the texture of surface	

TINTING BASES

White	168-0
P Base	168-1

FORMATS

	946ml	3.78L	18.9L
White	X	X	X
P Base	X	X	

STANDARDS

CGSB: Type 1GP 100, 209

COLOURS

A super white as well as a wide variety of off whites and pastel colours.

Base P (max. of 2 oz of colorant/ 3,78L)

USE	LIMITATIONS
<ul style="list-style-type: none"> - For interior use - Can be used on unpainted and painted surfaces - Recommended for walls and ceilings on which a flat finish is requested - Can be used for residential, commercial and institutional projects 	<ul style="list-style-type: none"> - Not for exterior use - Do not use on floors - Do not apply if temperature is below 10°C - Wait 15 days before the first wash

SURFACE PREPARATION

The surface must be dry and clean, with no traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

SUGGESTED PRIMER

Wood:	Seal pine knots with Stop Plus 298 prior to applying the finishing coat
Drywall:	Apply Latex Plus 170 primer & sealer
Masonry & concrete:	Apply Latex Plus 170 primer & sealer
Ferrous metal:	Apply ISO-RUST 4350 or 4370 rust-resistant primer
Flat latex & alkyd paint:	No primer required
Glossy alkyd paint:	Apply an undercoat of Adhero Plus 290

APPLICATION

Stir thoroughly before and during use. Apply one or two coats as required. Let dry 4 hours between coats for pale colours and 8 hours for dark colours. A 15mm lint free roller or a quality bristle brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with soapy lukewarm water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> -Keep away from children -Keep in a dry area between 10° C-30° C -Keep lid closed when not used. -Avoid freezing.

Dispose of the container in an environmentally-friendly manner.