



# Latex Field Marking Paint

# 195-0

## Technical Data Sheet

## White

### DESCRIPTION

White vinyl-acrylic copolymer paint for field

CHARACTERISTICS		TECHNICAL INFORMATION			
<p>Its highly visible white colour creates a sharp contrast when applied on natural turf, sand, asphalt, and concrete.</p> <p>Specially formulated to provide a good durability.</p> <p><b>Ecological</b> This paint contains zero COV* *(Volatile Organic Compound)</p>		<b>Drying Time</b>	Recoat: 30 min – 1h	To touch : 30 minutes	
			At 25° Celsius Relative humidity at 50% May differ depending on the colour		
		<b>Surface Coverage (for 18.9L)</b>	960 linear feet at 4 inches wide 5 mils wet May vary depending on the field		
		<b>Cleaning</b>	Lukewarm soapy water		
		<b>Dilution</b>	None		
		<b>Solids by Weight</b>	17%		
		<b>Solids by Volume</b>	7.5%		
		<b>VOC</b>	Zero		
<b>GLOSS</b>	60°	N/A			
	85°	N/A			
<b>N/A</b>	May vary according to the texture of surface to which it will be applied on				
TINTING BASES		FORMATS		COLOURS	
White	195-0	946ml	3.78L	18.9L	White
				X	
USE				LIMITATIONS	
<ul style="list-style-type: none"> <li>Specially manufactured for playground markings. This product may be used on natural and artificial turf, sand, asphalt and cement.</li> </ul>				<ul style="list-style-type: none"> <li>Do not use as a traffic paint.</li> </ul>	

## SURFACE PREPARATION

No preparation required.

## SUGGESTED PRIMER

No primer required.

## APPLICATION

Stir thoroughly before application. Upon request, the viscosity can be adjusted in advance.

**According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.**

**Dampen the grass, the colour pigments will more likely settle to be lighter following its application.** The paint will then dry to a whiter finish.

## WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

## CAUTION

- Keep away from children's reach
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

***Dispose of the container in an environmentally-friendly manner.***