



Technical Data Sheet

# MF-SOL

# 450-0

## Mineral Spirit

### DESCRIPTION

Mineral spirit based thinner refined for paints and varnishes.

CHARACTERISTICS	TECHNICAL INFORMATION	
Clear liquid with an odor of petroleum hydrocarbons	Density	0.786 kg/L
	Flash Point	42°C
	Aromatic	18%
	Kauri-Butanol	39
	Distillation	150-200°C
	Format	946ml, 3.78L & 18.9L
	Colour	Colourless
	Standard	Type 1 GP 4

USE	LIMITATIONS
<p><b>Thinner</b> Reduce the viscosity of alkyd resin based paints and varnishes.</p> <p><b>Cleaner</b> Clean stains and spatters as well as the tools used during the application of alkyd resin based paints and varnishes. Clean greasy contaminated surfaces prior to painting.</p> <p><b>Anti-film</b> Prevent the formation of skin in a partially used can of alkyd resin paint or varnish, during storage.</p>	<ul style="list-style-type: none"> <li>- Do not use with a latex paint, an alkyd paint or any specialised paint requiring a different thinner</li> </ul>

### THINNER

Reduce the lacquer in accordance with the chosen method of application and homogenize before use. It is normally reduced for spray applications.

### CLEANING

It is recommended to use a spin dryer to clean the rollers and paint brushes. For other tools use a rag or brush and wear gloves. MF-SOL 450 is also recommended as it is less flammable and safer to use when cleaning traffic paint residues.

### STORAGE

To prevent the formation of a film or top layer in a partially used container, cover the paint with a thin film layer of MF-440 before closing the container.

### WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

### CAUTION

- Keep away from children
- Maintain a good ventilation while applying
- Keep lid closed when not used.

***Dispose of the container in an environmentally-friendly manner.***