



METAL PLUS

Fast-dry Alkyd Primer Interior / Exterior



4950

Technical Data Sheet

DESCRIPTION

METAL PLUS 4950 is a universal fast dry Alkyd Primer with low VOC. It may be used on steel structures such as: roofs, reservoirs, steel beams, agricultural equipment and machinery. For all metal (indoors and outdoors), in the workshop or on the field. Protects against rust and corrosion. Use over any ordinary finish. Topcoat with **METAL PLUS 4800** rustproof coating. Offers a soft finish without sanding.

CHARACTERISTICS			TECHNICAL INFORMATION				
<p>Fast drying METAL PLUS 4950 is dry to the touch and can be recoated after only 15 to 30 minutes.</p>			Drying time	To touch: 15 to 30 minutes	Manipulation: 1 hour	Hard: 12 hours	Full cure : 7 days
			Theoretical Surface	432 to 472 sq. ft./ gallon 40 to 44 m ² / Litre Varies according to the porosity of the surface			
FORMATS			Cleaning				
	946 ml	3.78 L	Solvent 435				
4950	X	X	Thinner				
COLOURS			% de solids by weight				
4950	Grey		% de solids by volume				
USE			Density				
<ul style="list-style-type: none"> - For interior or exterior use. - Can be used on new and/or painted surfaces. - Recommended for steel structures such as: roofs, reservoirs, steel beams, agricultural equipment and machinery. 			VOC				
			Gloss				
			Flat				
			LIMITATIONS				
			- Must be covered.				
			- Can't be applied below 10°C.				

SURFACE PREPARATION

Surface must be clean, dry and free of all contaminants. Already painted surfaces: scrape all peeling paint paying particular attention to areas where rust has infiltrated. Remove rust with the help of a steel brush or sandpaper. Sand glossy areas. Remove wax, grease and oil using MF Paints thinner.

APPLICATION

MIX WELL BEFORE USING. Apply using a spray gun at a dry film thickness of 1 to 2 mils. Dilute 10% to 15 % with MF Paints thinner **453**. All applications must be done in a temperature (surface and air) of between 10°C to 32°C. Apply generously and uniformly. One coat is sufficient. Product viscosity: 70 ± 5 KU at 25°C.

IMPORTANT

For further security information about this product, please consult the Safety Data Sheet report.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep away from open flames or sparks
- Inflammable
- Flash point is between 10° C and 29° C

Dispose of the container in an environmentally-friendly manner.