



# Maintenance

# 5320-1

## Technical Data Sheet

## Semi-Gloss



### DESCRIPTION

**MAINTENANCE 5320** is a latex paint with a semi-gloss finish and an excellent opacity that is made to be used for residential and institutional projects.

CHARACTERISTICS		TECHNICAL INFORMATION		
<p><b>Non spattering</b> Only a minimum of protection is required to protect baseboards and floors during application.</p> <p><b>Superior Uniformity</b> Superior levelling properties enhance hiding and provide a smoother surface.</p> <p><b>Easy application</b> This paint is easy to apply and spreads easily.</p>	<b>Drying Time</b>	Recoat: 4 hours	To touch : 1 hour	
		At 25° Celsius Relative humidity at 50% May differ depending on the colour		
	<b>Surface Coverage (for 946 ml)</b>	12 – 14 m <sup>2</sup> (130 – 150 ft <sup>2</sup> )		
		May vary depending on the surface porosity		
	<b>Cleaning</b>	Lukewarm soapy water		
	<b>Dilution</b>	None		
	<b>Solids by Weight</b>	40%		
	<b>Solids by Volume</b>	33%		
	<b>VOC</b>	<50 g/L		
	<b>GLOSS</b>	60°	50%	
85°		75%		
<b>Semi-Gloss</b>	May vary according to the texture of surface			
TINTING BASES		FORMATS		STANDARDS
Base P	5320-1	946ml	3.78L 18.9L	
			X X	
COLOURS				
Base P (max. of 2oz of colorant/ 3.78L)				

USE	LIMITATIONS
<ul style="list-style-type: none"> <li>- For interior use</li> <li>- Can be used on unpainted and painted surfaces</li> <li>- Recommended for walls, doors and woodwork as well as for high level activity areas</li> <li>- Outdoor surfaces such as; wood, vinyl, aluminum, prepared masonry sidings or all other substrates</li> <li>- Can be used for residential and institutional projects</li> </ul>	<ul style="list-style-type: none"> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply on floors</li> <li>- Wait 15 days before first wash</li> </ul>

### SURFACE PREPARATION

The surface must be dry and clean, with no traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

### SUGGESTED PRIMER

<b>Wood:</b>	Seal pine knots with <b>Stop Plus 298</b> prior to applying the finishing coat
<b>Drywall:</b>	Apply <b>MAINTENANCE 5371-0</b> primer & sealer
<b>Masonry &amp; concrete:</b>	Apply <b>MAINTENANCE 5371-0</b> primer & sealer
<b>Ferrous metal:</b>	Apply <b>ISO-RUST 4350 or 4370</b> rust-resistant primer
<b>Flat latex &amp; alkyd paint:</b>	No primer required
<b>Glossy alkyd paint:</b>	Apply an undercoat of <b>Block Plus 296</b>

### APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 4 hours between coats. A 15mm lint free roller or a quality bristle brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with soapy lukewarm water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul>

***Dispose of the container in an environmentally-friendly manner.***