



# Maintenance

5335-0

Technical Data Sheet

Pearl



## DESCRIPTION

**MAINTENANCE 5335 series** is a latex paint with a Pearl finish and an excellent opacity that is made to be used for residential and institutional projects.

CHARACTERISTICS	TECHNICAL INFORMATION
-----------------	-----------------------

**Non spattering**  
Only a minimum of protection is required to protect baseboards and floors during application.

**Superior Uniformity**  
Superior levelling properties enhance hiding and provide a smoother surface.

**Easy application**  
This paint is easy to apply and spreads easily.

<b>Drying Time</b>	Recoat: 4 - 8 hours	To touch : 1 hour
	At 25° Celsius Relative humidity at 50% May differ depending on the colour	
<b>Surface Coverage (for 946 ml)</b>	12 – 13 m <sup>2</sup> (130 – 150 ft <sup>2</sup> ) May vary depending on the surface porosity	
<b>Cleaning</b>	Lukewarm soapy water	
<b>Dilution</b>	None	
<b>Solids by Weight</b>	43%	
<b>Solids by Volume</b>	33%	
<b>VOC</b>	<50 g/L	
<b>GLOSS</b>	60°	20%
	85°	50%
<b>Pearl</b>	May vary according to the texture of surface to which it will be applied on	

TINTING BASES	FORMATS	STANDARDS
---------------	---------	-----------

	946ml	3.78L	18.9L
White 5335-0		X	X
Base P 5335-1		X	X
Base M 5335-2		X	
Base D 5335-4		X	
Base A 5335-5		X	

## COLOURS

A super white as well as 1500 MF coloris. There are also an infinity of colours that can be reproduced by computer.

Base P (max. of 2 oz of colorant/ 3,78L)  
 Base M (max. of 5 oz of colorant/ 3,78L)  
 Base D (max. of 8 oz of colorant/ 3,78L)  
 Base A (max. of 12 oz of colorant/ 3,78L)

USE	LIMITATIONS
<ul style="list-style-type: none"> <li>- For interior use</li> <li>- Can be used on unpainted and painted surfaces</li> <li>- Recommended for walls, doors and woodwork as well as for high level activity areas</li> <li>- Can be used for residential and institutional projects</li> </ul>	<ul style="list-style-type: none"> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply on floors</li> <li>- Wait 15 days before first wash</li> </ul>

### SURFACE PREPARATION

The surface must be dry and clean, with no traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

### SUGGESTED PRIMER

<b>Wood:</b>	Seal pine knots with <b>Stop Plus 298</b> prior to applying the finishing coat
<b>Drywall:</b>	Apply <b>MAINTENANCE 5371-0</b> primer & sealer
<b>Masonry &amp; concrete:</b>	Apply <b>MAINTENANCE 5371-0</b> primer & sealer
<b>Ferrous metal:</b>	Apply <b>ISO-RUST 4350 or 4370</b> rust-resistant primer
<b>Flat latex &amp; alkyd paint:</b>	No primer required
<b>Glossy alkyd paint:</b>	Apply an undercoat of <b>Adhero Plus 290</b>

### APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry 4 hours between coats for pale colours and 8 hours for dark colours. A 15mm lint free roller or a quality bristle brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with soapy lukewarm water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul>

***Dispose of the container in an environmentally-friendly manner.***