



Technical Data Sheet

Proline ECO

Primer Sealer
Zero VOC



7070-0



DESCRIPTION

PROLINE ECO zero VOC 7070 is a primer sealer that does not contain any volatile organic compounds that can contribute to air pollution. It is made to seal new drywall.

CHARACTERISTICS		TECHNICAL INFORMATION					
<p><u>Zero VOC</u> This primer is ideal for LEED certified projects as well as for any other project requiring a zero VOC paint</p> <p><u>Excellent sealing properties</u> This product was developed to seal new drywall sheets and repairs, in order to obtain an even finish when applying the top coat.</p> <p><u>Hiding properties</u> This product has a very good opacity.</p> <p><u>Sanding</u> Easy to sand after 3 hours without overloading the sandpaper.</p> <p><u>Non spattering</u> Only a minimum of protection is required to protect baseboards and floors during application.</p>		<p>Drying Time</p> <table border="1"> <tr> <td>Recoat:</td> <td>4 hours</td> <td>To touch :</td> <td>1 hour</td> </tr> </table> <p>At 25° Celsius Relative humidity at 50% May differ depending on the colour</p>	Recoat:	4 hours	To touch :	1 hour	
Recoat:	4 hours	To touch :	1 hour				
		<p>Surface Coverage (for 946 ml)</p> <p>8.2 – 10.5 m² (88 -113ft²) May vary depending on the surface porosity</p>					
		<p>Cleaning</p> <p>Lukewarm soapy water</p>					
		<p>Dilution</p> <p>None</p>					
		<p>Solids by Weight</p> <p>61%</p>					
		<p>Solids by Volume</p> <p>43%</p>					
		<p>VOC</p> <p>Zero</p>					
		<p>GLOSS</p> <table border="1"> <tr> <td>60°</td> <td>N/A</td> </tr> <tr> <td>85°</td> <td>N/A</td> </tr> </table>	60°	N/A	85°	N/A	
60°	N/A						
85°	N/A						
		<p>N/A</p> <p>May vary according to the texture of surface to which it will be applied on</p>					
TINTING BASES		FORMATS		STANDARDS			
White	7070-0	946ml	3.78L	18.9L			
			X	X			
				<p>MPI: Certified category #149, GPS-1, GPS-2 (Master Paint Institute)</p> <p>Green Seal: Type GS-11</p>			
COLOURS							
White		<p>CGSB: Type 1GP 119</p> <p>CFIA: Product approved (Canadian Food Inspection Agency)</p>					

USE	LIMITATIONS
<ul style="list-style-type: none"> - For interior use - Suitable for new surfaces such as; drywall, concrete and wood - Seals and hides repairs in order to obtain an even finish with the top coat - Suitable for residential or institutional projects 	<ul style="list-style-type: none"> - Do not apply if temperature is below 10°C - Not for exterior use - Do not apply on floors - Do not apply over alkyd paints - Do not apply on pearl finish or glossier surfaces

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 4 hours between each coat. A 15mm lint free roller or a quality nylon-polyester brush are recommended to enhance its application. For a spray application, dilute with a maximum of 10% water. Clean brushes and rollers with lukewarm soapy water.

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> -Keep away from children -Keep in a dry area between 10° C-30° C -Keep lid closed when not used. -Avoid freezing.

Dispose of the container in an environmentally-friendly manner.