



Technical Data Sheet

DRYFALL PAINT

753 Series

100% Acrylic Flat Black

DESCRIPTION

A latex **100% acrylic** based dryfall paint developed for spraying factory and warehouse ceilings.

CHARACTERISTICS

When applied at a height exceeding 18 feet, with less than 50% humidity level, any dryfall paint particles that have fallen to the floor may be swept away with a broom or vacuumed.

This paint develops a chemical bond with the metal which makes it extremely difficult to scratch down to bare metal.

This latex based product emits a very faint odour and is not a fire hazard.

This dryfall paint will prevent flash rust from appearing on the surface during the application.

Not a health hazard

This paint does not contain crystalline silica.

TECHNICAL INFORMATION

Drying Time	Recoat: 4 hours	To touch: 1 hour
	At 25° Celsius Relative humidity at 50%	
Surface Coverage (for 946 ml)	70 m ² (750 pi ²) for steel deck ceilings with ceiling joists	
	140 m ² (1500 pi ²) for a flat ceiling	
Cleaning	Lukewarm soapy water	
Dilution	None	
Solids by Weight	48%	
Solids by Volume	36%	
VOC	< 150 g/L	
GLOSS	60°	2%
	85°	3%
Flat	May vary according to the texture of surface to which it will be applied on	

TINTING BASES

Black 753-0

FORMATS

946ml 3.78L 18.9L
X

STANDARDS

COLOURS

Black

USE

- For interior use
- Developed for galvanized steel or other metal ceilings with more than 18 feet high
- Can be used on bare or painted surfaces
- Suitable for both commercial or institutional projects

LIMITATIONS

- Do not apply if temperature is below 10°C
- Will not protect against rust in a humid area
- Depending on the height of the ceiling, it is preferable to cover the floor, when the relative humidity is higher than 50%.

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

SUGGESTED PRIMER

No primer required.

APPLICATION

Stir thoroughly before applying. It is important to keep the moisture content below 50% throughout the application. This is to keep the dry fall properties at 18 feet.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

Dispose of the container in an environmentally-friendly manner.