

**ADDITIVE****TECHNICAL DATA****CS-37****RUST-OLEUM®**

# 200 ANTI-SKID FLOOR COATING ADDITIVE

**DESCRIPTION AND USES**

The 200 Anti-Skid Floor Coating Additive is a specially refined aggregate to provide a surface texture to floor coatings and promote skid resistance of the dry coating.

**APPEARANCE**

Off white particles or granules

**PRODUCTS**

SKU	Description
200504	Anti-Skid Floor Coating Additive

**RECOMMENDED COATINGS**

Any floor coating with a dry film thickness of 16 mils or less.

**PACKAGING**

One pound bags.

**PRODUCT APPLICATION**

When used with thin film coatings (DFT 2-5 mils per coat), the 200 Anti-Skid Floor Coating Additive can be mixed directly into the coating. Use one pound of additive per gallon of coating. Stir the container frequently to ensure the additive doesn't settle out. Apply the coating by roller.

When using with a high build coating (DFT 5-16 mils per coat), best results are achieved by broadcasting the additive over the freshly applied floor coating, then back roll to incorporate into the film.

**PHYSICAL PROPERTIES**

Physical Properties		200 ANTI-SKID FLOOR COATING ADDITIVE
<b>Composition</b>		Crystalline Silica
<b>Weight</b>	<b>Per Gallon</b>	19.6 lbs.
	<b>Per Liter</b>	2.35 kg
<b>Solids</b>	<b>By Weight</b>	100%
	<b>By Volume</b>	100%
<b>Packaging</b>		One pound bags
<b>Shelf Life</b>		5 years
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.