

#### SAFETY DATA SHEET (SDS)

Section 1. Identification				
Product identifier 4000-	1, -2, -4			
Other means of identification ISO-RUST, rust resistant pain, alkyd based, P Base, M Base, D Base				
Recommended use and restrictions on use For metal surfaces				
Initial supplier identifier MF Paints Inc. 1605 Dagenais Boulevard W, Laval, QC H7L 5A3 T:(450) 628-3831				
Emergency telephone numb	er/restriction on use   Canada – CANUTEC 24 hour number 613-996-6666			

#### Section 2. Hazard identification

#### Classification of hazardous product (name of the category or subcategory of the hazard class)

Flammable liquid (Category 3)

Skin irritation (Category 2)

Eye irritation (Category 2A)

Specific target organ toxicity – single exposure (Category 3), Central nervous system

Carcinogenicity (Category 2)

# Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)







### Danger

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bound container and receiving equipment. P241 Use explosion-proof equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P302 + P352 IF ON SKIN: wash with plenty of water. P332 + P313 IF SKIN irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell P308 + P313 IF exposed or concerned: Get medical attention. P370 + P378 In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish. P403 + P233 + P235 Store in a well-ventilated place. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known None					
Section 3. Composition/information on ingredients					
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*			
Medium aliphatic solvent naphtha	64742-88-7	< 5			
Titanium dioxide	13463-67-7	< 30			
Aromatic petroleum distillates	64742-95-6	< 5			
Kerosene	64742-47-8	< 5			
Stoddard solvent	8052-41-3	< 20			
Xylene	1330-20-7	< 1			
Silica crystalline, Quartz	14808-60-7	< 0.1			
Trizinc bis(orthophosphate)	7779-90-0	< 1			
Zinc oxide	1314-13-2	<1			
Methanol	67-56-1	<0.5			
Propylene glycol mono butyl ether	5131-66-8	< 0.5			
[3-(2,3-epoxypropoxy) propyl] trimetoxysilane	2530-83-8	< 1			
* Statement - This safety data sheet provides concentration range(s	s) instead of the actual concentration(s) considered to	rade secret(s).			



Section 4. First-aid measures				
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.			
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is			
	rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two			
	glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.			
Skin contact	IF ON SKIN: wash with plenty of water. (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off			
	contaminated clothing and wash it before reuse.			
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue			
rinsing. If eye irritation persists: Get medical attention.				
Most important symptoms and effects (acute or delayed)		Causes skin irritation. Causes serious eye irritation.		
Indication of immediate medical attention/special treatment		In all cases, call a doctor. Do not forget this document.		
Section 5. Fire-fighting measures				

#### Section 5. In e-righting i

Specific hazards of the hazardous product (hazardous combustion products) Carbon oxides and other irritant/toxic gases and fumes.

# Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

# Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

## Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

## Methods and materials for containment and cleaning up

Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

# Section 7. Handling and storage

#### **Precautions for safe handling**

Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

# Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

# Section 8. Exposure controls/Personal protection

# Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 13463-67-7 ACGIH – TLV-TWA 10 mg/m³ & PEL-TWA 10 mg/m³; DUST ACGIH – TLV-TWA 1 mg/m³ & PEL-TWA 5 mg/m³ (respirable fraction) & 15 mg/m³ (total dust); CAS 8052-41-3 – ACGIH – TLV-TWA 100 ppm & PEL-TWA 500 ppm; CAS 14808-60-7 ACGIH – TLV-TWA 0.025 mg/m³ & PEL-TWA 0.1 mg/m³; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 1314-13-2 ACGIH-TLV-TWA 2mg/m³ (breathable particles)

### **Appropriate engineering controls**

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

## Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.



Section 9. Physical	and chemical properties					
Appearance, physical state/colour Liquid	Vapour pressure Not available					
Odour Characteristic	Vapour density Not available					
Odour threshold Not available	<b>Relative density</b> 4000-1=1.17 g/L -2=1.15 g/L -4=1.02 g/L					
pH Not available	Solubility Not available					
Melting/freezing point Not available	Partition coefficient - n- Not available octanol/water					
Initial boiling point/range Not available	Auto-ignition temperature Not available					
Flash point 34°C closed cup	<b>Decomposition temperature</b> Not available					
Evaporation rate Not available	Viscosity 4000-1 = 600 cSt @ 40°C   -2 = 460 cSt @ 40°C   -4 = 300 cSt @ 40°C   40°C					
Flammability (solids and gases) Not available	VOC Not available					
Upper and lower flammability/explosive limits Not available	Other None known					
Section 10. Sta	bility and reactivity					
Reactivity						
Does not react under the recommended storage and handling conditions pro-	escribed.					
Chemical stability						
Stable under the recommended storage and handling conditions prescribed						
Possibility of hazardous reactions						
Keep away from heat, hot surfaces, sparks, open flames and other ignition Conditions to avoid (static discharge, shock or vibration)	n sources. No smoking. Take action to prevent static discharges.					
Keep away from heat, hot surfaces, sparks, open flames and other ignition	n sources. No smoking. Take action to prevent static discharges					
Incompatible materials	in sources. The smoking. Take action to prevent static discharges.					
Oxidizing materials; etc.						
Hazardous decomposition products						
None known						
2 70.000 20.000 77.00	anlogical information					
	cological information					
Information on the likely routes of exposure (inhalation, ingestion, sl						
Causes skin irritation. Causes serious eye irritation. May cause drowsine  Symptoms related to the physical, chemical and toxicological charac						
Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.						
Delayed and immediate effects (chronic effects from short-term and						
Ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxic	lata available; Germ Cell Mutagenicity – No data available; Carcinogenicity – city – No data available; Specific Target Organ Toxicity — Single Exposure – data available; Aspiration Hazard – No data available; Health Hazards No					
Otherwise Classified – No data available.	data avanable, Aspiration Hazard – No data avanable, Heatin Hazards No					
Numerical measures of toxicity (ATE; LD <sub>50</sub> & LC <sub>50</sub> )						
CAS 1330-20-7 Oral, rat LD <sub>50</sub> 4300 mg/kg; Dermal, rabbit LD <sub>50</sub> 12100 mg/kg;	ng/kg; CAS 64742-95-6 Oral, rat LD <sub>50</sub> 8400 mg/kg;					
ATE not available in this document.						
CAS 7779-90-0 Oral rat LD <sub>50</sub> >5000 mg/kg; CAS 1314-13-2 Oral rat LD <sub>50</sub> 3130 mg/kg; CAS 6756-1 Oral rat LD <sub>50</sub> 5626 mg>kg; Dermal rabb	050 7950 mg/kg; CAS 5131-66-8 Oral rat LD50 3300 mg>kg; Dermal rabbit					
	ological information					
Ecotoxicity (aquatic and terrestrial information) No data available	for the product.					
Persistence and degradability No data available						
Bioaccumulative potential No data available						
Mobility in soil No data available						
Other adverse effects No data available						
	posal considerations					
Information on safe handling for disposal/methods of disposal/contaminated packaging						
Dispose of contents/container into safe container in accordance with local, regional or national regulations.						
Section 14. Transport information						
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations						
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III						
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)						
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III	UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III					
	UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)					
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III						



Special precautions (transport/conveyance) May also be shipped as a LIMITED QUANTITY in accordance with TDG.

Environmental hazards (IMDG or other) None

Bulk transport (usually more than 450 L in capacity) Possible

	Section 15. Regulatory information			
Safety/health C	Canadian regulations specifics Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).			
Environmental Canadian regulations specifics   Refer to Section 3 for ingredient(s) of the DSL				
Safety/health/environmental outside regulations specifics				
United States OSHA information: This product is regulated according to OSHA (29 CFR).				
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.				
United States TCSA information: Refer to the ingredients listed in Section 3.				
California Propos	osition 65: This product contains an ingredient known to the State of California to cause cancer or other reproductive harm.			
Section 16. Other information				
Date of the latest revision of the safety data sheet   August 14, 2018 version 1 (NSS ENTREPRISE INC.)				
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.			
Abbreviations				
ACGIH	American Conference of Governmental Industrial Hygienists			
ATE	Acute toxicity estimate			
CAS	Chemical Abstract Service			
DSL	Domestic Substance List			
IARC	International Agency for Research on Cancer			
IATA	International Air Transport Association			
IMDG	International Maritime Dangerous Goods Code			
LC	Lethal concentration			
LD	Lethal Dosage			
NIOSH	National Institute for Occupational Safety and Health			
NTP	National Toxicology Program (U.S.A.)			
OSHA	Occupational Safety and Health Administration (U.S.A.)			
PEL	Permissible Exposure Limit			
STEL	Short-term Exposure Limit			
TDG	Transport of dangerous goods in Canada			
TLV	Threshold Limit Value			
TSCA	Toxic Substances Control Act			
TWA	Time Weighted Average			
WHMIS	Workplace Hazardous Materials Information System			

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.