

SAFETY DATA SHEET (SDS)

Section 1. Identification		
Product identifier	4350-0	
Other means of identification	ISO-RUST, Alkyd-based anti-rust. Primer. Gray	
Recommended use and restrictions on use	For metal surfaces	
Initial supplier identifier	MF Paints Inc. 1605 Dagenais Boulevard W, Laval, QC H7L 5A3 T:(450) 628-3831	
Emergency telephone number/restriction on use	Canada – CANUTEC 24 hour number 613-996-6666	
Section 2. Hazard identification		
Classification of hazardous product (name of the category or subcategory of the hazard class)		
Flammable liquid (Category 3) Skin irritation (Category 2) Eye irritation (Category 2A) Specific target organ toxicity – single exposure (Category 3), Central nervous system Carcinogenicity (Category 2)		
Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)		
		
Danger H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bound container and receiving equipment. P241 Use explosion-proof equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P302 + P352 IF ON SKIN: wash with plenty of water. P332 + P313 IF SKIN irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. . P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell P308 + P313 IF exposed or concerned: Get medical attention. P370 + P378 In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish. P403 + P233 + P235 Store in a well-ventilated place. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.		
Other hazards known	None	
Section 3. Composition/information on ingredients		
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*
Aliphatic Hydrocarbon	64742-49-0	< 6
Titanium dioxide	13463-67-7	< 6
Toluene	108-88-3	< 1
Zinc Oxide	1314-13-2	< 2
Stoddard solvent	8052-41-3	< 1
Xylene	1330-20-7	< 1
Silica crystalline, Quartz	14808-60-7	< 0.3
Nepheline Syenite	37244-95-5	15-25
TriZinc bis orthophosphate	7779-90-0	< 5
1,2,4-Trimethylbenzene	95-63-6	< 2
* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).		

Section 4. First-aid measures	
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Skin contact	IF ON SKIN: wash with plenty of water. (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Most important symptoms and effects (acute or delayed)	Causes skin irritation. Causes serious eye irritation.
Indication of immediate medical attention/special treatment	In all cases, call a doctor. Do not forget this document.
Section 5. Fire-fighting measures	
Specific hazards of the hazardous product (hazardous combustion products)	
Carbon oxides and other irritant/toxic gases and fumes.	
Suitable and unsuitable extinguishing media	
In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.	
Special protective equipment and precautions for fire-fighters	
During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.	
Section 6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	
Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).	
Methods and materials for containment and cleaning up	
Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.	
Section 7. Handling and storage	
Precautions for safe handling	
Wear gloves/protective clothing/eye protection/face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.	
Conditions for safe storage, including any incompatibilities	
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.	
Section 8. Exposure controls/Personal protection	
Control parameters (biological limit values or exposure limit values and source of those values)	
Exposure limits: CAS 13463-67-7 ACGIH – TLV-TWA 10 mg/m ³ & PEL-TWA 10 mg/m ³ ; DUST ACGIH – TLV-TWA 1 mg/m ³ & PEL-TWA 5 mg/m ³ (respirable fraction) & 15 mg/m ³ (total dust); CAS 8052-41-3 – ACGIH – TLV-TWA 100 ppm & PEL-TWA 500 ppm; CAS 14808-60-7 ACGIH – TLV-TWA 0.025 mg/m ³ & PEL-TWA 0.1 mg/m ³ ; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm;	
Appropriate engineering controls	
Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.	
Individual protection measures/personal protective equipment	
Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.	

Section 9. Physical and chemical properties			
Appearance, physical state/colour	Liquid	Vapour pressure	Not available
Odour	Characteristic	Vapour density	Not available
Odour threshold	Not available	Relative density	1.331 g/L
pH	Not available	Solubility	Not available
Melting/freezing point	Not available	Partition coefficient - n-octanol/water	Not available
Initial boiling point/range	Not available	Auto-ignition temperature	Not available
Flash point	34°C closed cup	Decomposition temperature	Not available
Evaporation rate	Not available	Viscosity	378 cSt @ 40°C
Flammability (solids and gases)	Not available	VOC	< 200 g/l
Upper and lower flammability/explosive limits	Not available	Other	None known
Section 10. Stability and reactivity			
Reactivity			
Does not react under the recommended storage and handling conditions prescribed.			
Chemical stability			
Stable under the recommended storage and handling conditions prescribed.			
Possibility of hazardous reactions			
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.			
Conditions to avoid (static discharge, shock or vibration)			
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.			
Incompatible materials			
Oxidizing materials; etc.			
Hazardous decomposition products			
None known			
Section 11. Toxicological information			
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)			
Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.			
Symptoms related to the physical, chemical and toxicological characteristics			
Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.			
Delayed and immediate effects (chronic effects from short-term and long-term exposure)			
Skin Sensitization – No data available; Respiratory Sensitization – No data available; Germ Cell Mutagenicity – No data available; Carcinogenicity – Ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – No data available; Specific Target Organ Toxicity — Single Exposure – Possible; Specific Target Organ Toxicity — Repeated Exposure – No data available; Aspiration Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.			
Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)			
CAS 1330-20-7 Oral, rat LD ₅₀ 4300 mg/kg; Dermal, rabbit LD ₅₀ 12100 mg/kg; CAS 64742-95-6 Oral, rat LD ₅₀ 8400 mg/kg; ATE not available in this document.			
Section 12. Ecological information			
Ecotoxicity (aquatic and terrestrial information)		No data available for the product.	
Persistence and degradability		No data available	
Bioaccumulative potential		No data available	
Mobility in soil		No data available	
Other adverse effects		No data available	
Section 13. Disposal considerations			
Information on safe handling for disposal/methods of disposal/contaminated packaging			
Dispose of contents/container into safe container in accordance with local, regional or national regulations.			
Section 14. Transport information			
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations			
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III			
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)			
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III			
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)			
UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III			
Special precautions (transport/conveyance)		May also be shipped as a LIMITED QUANTITY in accordance with TDG.	
Environmental hazards (IMDG or other)		None	
Bulk transport (usually more than 450 L in capacity)		Possible	



Section 15. Regulatory information	
Safety/health Canadian regulations specifics	Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).
Environmental Canadian regulations specifics	Refer to Section 3 for ingredient(s) of the DSL
Safety/health/environmental outside regulations specifics	
United States OSHA information: This product is regulated according to OSHA (29 CFR).	
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.	
United States TCSA information: Refer to the ingredients listed in Section 3.	
California Proposition 65: This product contains an ingredient known to the State of California to cause cancer or other reproductive harm.	
Section 16. Other information	
Date of the latest revision of the safety data sheet	August 14, 2018 version 1 (NSS ENTREPRISE INC.)
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.
Abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.	