



Technical Data Sheet

# ISO-TEX

205-0

Textured

## DESCRIPTION

ISO-TEX 205 series is a textured decorative emulsified latex resin based coating made with granular volcanic stone matter.

| CHARACTERISTICS   |                                      | TECHNICAL INFORMATION   |                   |           |                    |
|---|--------------------------------------|---|-------------------|-----------|--------------------|
| <p><b>Block filler</b><br/>Its strong consistency allows irregular surface cavities to be filled and sealed.</p> <p><b>Rustic appearance</b><br/>Dries to a rich textured and granular rustic appearance.</p> <p><b>Ecological</b><br/>This paint has a low VOC* content (&lt; 50 g/L)<br/>*(Volatile Organic Compound)</p> | <b>Drying Time</b>                   | Recoat: 2-4 hours   | To touch : 1 hour |           |                    |
|   | <b>Surface Coverage (for 946 ml)</b> | 1.2 – 2.4 m <sup>2</sup> (12.5 – 25 ft <sup>2</sup> )<br>May vary depending on the surface porosity |                   |           |                    |
|   | <b>Cleaning</b>                      | Lukewarm soapy water  |                   |           |                    |
|   | <b>Dilution</b>                      | None  |                   |           |                    |
|   | <b>Solids by Weight</b>              | 72%   |                   |           |                    |
|   | <b>Solids by Volume</b>              | 57%   |                   |           |                    |
|   | <b>VOC</b>                           | <50 g/L   |                   |           |                    |
|   | <b>GLOSS</b>                         | 60°   | N/A               |           |                    |
|   |                                      | 85°   | N/A               |           |                    |
|   | <b>N/A</b>                           | May vary according to the texture of surface to which it will be applied on                         |                   |           |                    |
| TINTING BASES   |                                      | FORMATS   |                   | STANDARDS |                    |
| White   | 205-0                                | 946ml   | 3.78L             | 18.9L     | CGSB: Type 1GP 162 |
|   |                                      |   | X                 | X         |                    |
| COLOURS   |                                      |   |                   |           |                    |
| White   |                                      |   |                   |           |                    |

| USE  | LIMITATIONS   |
|--|---|
| <ul style="list-style-type: none"> <li>- For interior and exterior use</li> <li>- Specifically made for house foundations and ceilings</li> <li>- Suitable for residential, commercial and institutional projects</li> </ul> | <ul style="list-style-type: none"> <li>- Do not apply if temperature is below 10°C</li> <li>- Do not apply on floors</li> </ul> |

### SURFACE PREPARATION

The surface must be dry and clean, without traces of dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

On new or treated wood having been exposed to inclement weather, it is highly recommended to neutralise all mildew, visible or not, in order to avoid peeling. Use a mix of 3 parts water for 1 part bleach, let this work for 20 minutes, then rinse; allow the wood to dry for at least 24 hours.

### SUGGESTED PRIMER

|                                      |   |
|--------------------------------------|---|
| <b>Wood:</b>                         | Apply an undercoat of <b>Portico 270 series</b>                           |
| <b>Drywall:</b>                      | Apply <b>Latex Plus 170</b> primer & sealer                               |
| <b>Masonry &amp; concrete:</b>       | Apply <b>Latex Plus 170</b> primer & sealer                               |
| <b>Exterior masonry:</b>             | Apply an undercoat of <b>Portico 270</b> prior to applying finishing coat |
| <b>Ferrous metal:</b>                | Apply <b>ISO-RUST 4350 or 4370</b> rust-resistant primer                  |
| <b>Flat latex &amp; alkyd paint:</b> | No primer required  |
| <b>Glossy alkyd paint:</b>           | Apply an undercoat of <b>Adhero Plus 290</b>                              |

### RECOMMENDED FINISH

Should this product be applied outdoors, cover up the **ISO TEX** with **ISO-STAIN 850 series** opaque stain.

### APPLICATION

Stir thoroughly before use. Apply evenly with a long hair roller and be sure to always finish the last motion of the roller in the same direction. If required, even out the wet surface with the roller without adding **ISO-TEX**.

| WARRANTY   | CAUTION  |
|--|--|
| <p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p> | <ul style="list-style-type: none"> <li>-Keep away from children</li> <li>-Keep in a dry area between 10° C-30° C</li> <li>-Keep lid closed when not used.</li> <li>-Avoid freezing.</li> </ul> |

***Dispose of the container in an environmentally-friendly manner.***