



BLOCK FILLER

206-0

For cement blocks

Technical Data Sheet

DESCRIPTION

BLOCK FILLER 206 series is an emulsified latex based primer sealer (block filler) for concrete blocks.

CHARACTERISTICS		TECHNICAL INFORMATION		
<p>Block filler Its strong consistency allows irregular surface cavities to be filled and sealed.</p> <p>Excellent sealer Seals the surface in order to obtain an even finish with the topcoat of paint.</p> <p>Ecological This paint has a low VOC* content (< 50 g/L) *(Volatile Organic Compound)</p>	Drying Time	Recoat: 2-4 hours	To touch : 1 hour	
		At 25° Celsius Relative humidity at 50% May differ depending on the colour		
	Surface Coverage (for 946 ml)	4 – 6 m ² (43 – 65 ft ²) May vary depending on the surface porosity		
	Cleaning	Lukewarm soapy water		
	Dilution	None		
	Solids by Weight	65-70 %		
	Solids by Volume	50-53 %		
	VOC	<100 g/L (type MPI E range=3)		
	GLOSS	60°	2.5%	
		85°	4.5%	
FLAT	May vary according to the texture of surface to which it will be applied on			
TINTING BASES		FORMATS		
White	206-0	946ml	3.78L 18.9L X	
COLOURS		STANDARDS		
White		CGSB: Type 1GP 188		
		CFIA: Product approved <i>(Canadian Food Inspection Agency)</i>		

USE	LIMITATIONS
<ul style="list-style-type: none"> - For interior use. If used outdoors it must be covered with the proper topcoat. - Recommended for concrete block walls - Suitable for residential, commercial and institutional projects 	<ul style="list-style-type: none"> - Do not apply if temperature is below 10°C - Do not apply on floors

SURFACE PREPARATION

The surface must be dry and clean, without traces of dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) in order to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting.

APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 2 hours or more between coats. In order to properly seal the surface, the use of a 15mm lint free roller or a quality polyester/nylon brush are recommended. For a spray application, dilute with a maximum of 10% water. If sprayed, roll over with a wet roller before the surface dries to enhance penetration of the surface cavities. Clean brushes and rollers with soapy lukewarm water.

Note: Use an airless pump with a minimum 0.021inch opening. Remove the pump and the gun filters

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> -Keep away from children -Keep in a dry area between 10° C-30° C -Keep lid closed when not used. -Avoid freezing.

Dispose of the container in an environmentally-friendly manner.