



Stain Killing Primer 295

Primer
Low odor
Synthetic Polymer

TECHNICAL DATA SHEET

DESCRIPTION

Stain Killing Primer 295 is a synthetic polymer based primer, made with low odor solvent. It dries quickly and is for indoor use. This primer is made for surfaces that had water, smoke and fire damage. it will cover stains. **Stain Killing Primer 295** can be used for commercial, maintenance and residential projects.

| USE | LIMITATIONS |
|--|---|
| This primer is applicable on interior surfaces. Stain Killing Primer 295 must be applied onto water based painted surfaces that have been properly prepared. It is recommended for water and smoke stains, ink, pencil, lipstick as well as burnt surfaces. Given the diversity of the stains, we suggest to apply two coats for an optimal result. | <p>Do not apply outside.</p> <p>Remove, whenever possible, all stains with a remover solution.</p> <p>Should there be presence of nicotine, 2 coats of Stain-Killing 295 will be necessary in order to prevent bleeding of the stain.</p> <p>Not designed to block smoke odour</p> <p>Do not apply a thick coat with a spray gun, as the paint film could crackle</p> <p>Do not mix with other paints</p> <p>Can't be used as a wallpaper primer.</p> <p>Not designed to seal gypsum board or drywall compound.</p> <p>If the topcoat requires a solvent based paint, the Stain-killing 295 must previously be covered with a coat of latex primer.</p> |

| CARACTERISTICS | TECHNICAL INFORMATION | | |
|---|---|--|------------|
| <ul style="list-style-type: none"> • Stain Killing Primer 295 blocks most stains in one or two coats. • For water-damaged surfaces. • For fire-damaged surfaces • For smoke-damaged surfaces. • For blocking ink, pencil and lipstick stains. • Must be applied on a water based paint only. • Can be covered after one hour only. • To completely eliminate odours following a fire, an ozone purging method should be carried out by professionals, inside the walls, before applying a Stain killing primer. | DRYING TIME | Recoat: | To touch: |
| | | 1 hour | 30 minutes |
| | At 25° Celsius Relative humidity at 50% | | |
| | SURFACE COVERAGE (for 3.78 L) | 30 - 40 m ² (325 - 430 ft ²) May vary depending on the surface | |
| | Recommended film thickness | Wet : 3,7 - 5,0 mils Dry: 2,0 - 2,7 mils | |
| | Cleaning | Miniral spirit (MF-SOL 450) | |
| | Resin | Alkyd | |
| | Inflammability | Yes | |
| | Flash point | 42 °C | |
| | % of solids by weight | 78% | |
| % of solids by volume | 55% | | |
| VOC | <350 g/L | | |
| GLOSS | 60° | N/A | |
| | 85° | N/A | |

| TINTING BASES | | | | |
|---------------|--------|--------|--------|--|
| | 946 ml | 3,78 L | 18,9 L | |
| 295-0 White | X | X | X | |

| SURFACE PREPARATION | |
|--|--|
| <p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p>Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> | |
| APPLICATION | MAINTENANCE |
| <p>This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with mineral spirit (MF-SOL 450) following their use.</p> <p>For spray application : Pressure : 2000 to 2500 lb/in²* Nozzle : 0.015 – 0.019*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p> | <p>Must be topcoated with a water based paint.</p> |
| | STORAGE |
| | <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p> |

| WARRANTY | CAUTION |
|--|--|
| <p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p> | <ul style="list-style-type: none"> • Keep away from children's reach • Keep lid closed when not in use • Avoid freezing |

" Contact your municipality to dispose of the container in an environmentally-friendly manner "