



Thinner / Cleaner

Technical Data Sheet

435-0

DESCRIPTION

Xylene based thinner for swimming pool paint as well as for solvent based epoxy. Can be used for tools clean-up.

CHARACTERISTICS	TECHNICAL INFORMATION	
Clear liquid with an odor of petroleum hydrocarbons	Density	0.87 kg/L
	Flash Point	27°C
	Aromatic	100%
	Kauri-Butanol	99
	Format	946ml, 3.78L & 18.9L
	Colour	Colourless
	Standard	Type 1 GP 94
USE	LIMITATIONS	
<p>Thinner Reduce swimming pool paint viscosity as specified</p> <p>Cleaner Clear all swimming pool paint or solvent based epoxy residues on tools following the application of the products.</p>	<p>- Do not use with a latex paint, an alkyd paint or any specialised paint requiring a different thinner</p>	

THINNER

Reduce the lacquer in accordance with the chosen method of application and homogenize before use. It is normally reduced for the first coat.

CLEANING

It is recommended to use a spin dryer to clean the rollers and paint brushes. For other tools use a rag or brush and wear gloves.

WARRANTY	CAUTION
This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.	<ul style="list-style-type: none"> -Keep away from children -Maintain a good ventilation while applying -Keep lid closed when not used. -Dry rags properly, *do not dispose of them if they are still humid.

Dispose of the container in an environmentally-friendly manner.