



Technical Data Sheet

**Description**

Proline 6065 is an acrylic latex primer sealer for interior use. It is easy to apply and dries quickly. It is formulated to seal new drywall and porous concrete surface. It was developed to answer the needs of professional painters. The Proline 6065 can be used for commercial, industrial and residential projects.

**Use**

This primer sealer is applicable on interior surfaces. It seals and hides repairs in order to obtain a uniform finish once the topcoat is applied. Proline 6065 is recommended for new surfaces such as drywall, concrete, and wood.

**Advantages**

- Seals drywall and joint compound
- It dries quickly and can be top coated after only 3 hours.
- It provides a good hiding
- Can easily be sanded after a drying time of 4 hours without overloading the sanding paper.

**Limitations**

- Avoid application in all temperatures under 10°C
- Not for exterior application
- Do not use on flooring
- Do not apply on alkyd paint
- Do not apply on glossy surfaces
- May crack if overloaded in the corners

**Technical Data**

Resin	Acrylic Latex		
Color	White		
Cleaning	Water		
Flash point	N/A		
Inflammability	N/A		
Solids by weight	54+/-2	%	
Solids by volume	37+/-2	%	
VOC	<50	g/l	
Gloss	60°	N/A	%
Sheen	85°	N/A	%
Standards	CGSB Type IGP 119		

**Application Data**

<b>At 25° Celsius</b>			
<b>Relative humidity at 50%</b>			
<b>May differ depending on the colour</b>			
<b>Spreading Rate</b>	May	33-42 m2 (350-450sqft)	gallon
<small>vary depending on the surface</small>			
<b>Film Thickness</b>	Wet	3,6-4,6	mils
	Dry	1,33-1,70	mils
<b>Drying Time</b>	Tack free	30	min
	Recoat	4	hours
	Cleaning	30	days
	Light	30	hours
<b>Application</b>	Brush	√	
	Roller	15	mm
	Spray* Nozzle : 0.017 – 0.021*	2000-2500	lb/po <sup>2</sup>
<small>* These data may vary depending on the equipment manufacturer</small>			
<b>Exterior</b>	N/A		
<b>Storage</b>	Temperature	10-30	°C
<b>Tinted Bases</b>	<b>Formats</b>		
	946ml	3,78L	18,9L
6065-0 White		√	√
<b>Recommended Primers</b>			
N/A			



# 6065

## Primer Sealer Acrylic latex

INTERIOR

## Technical Data Sheet

### Surface Preparation

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

**Presence of mold:** Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

**Flaking or peeling paint:** Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth.

A repair compound should be used to fill holes and uneven surfaces. Sand with a grade #100 sanding paper.

**New drywall:** To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.

**Concrete / Masonry:** Wait until the concrete and/or masonry has cured at least 30 days before painting it.

**Wood:** The surface must be sanded with a grade #80 or #100 sanding paper to improve adhesion.

### Application

This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colours and 8 hours for dark colours. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.

**For spray application:** May be diluted with a maximum of 10% water.

**Pressure:** 2000 to 2500 lb/in<sup>2</sup>\*

**Nozzle:** 0.017 – 0.021\*

\*This data may vary depending on the brand of the equipment manufacturer.

### Maintenance

Must be top coated.

### Warranty

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

### Caution

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

**Contact your municipality to dispose of the container in an environmentally-friendly manner.**