



# 7050 SERIES

Ceiling flat  
Self-Priming  
Zéro COV  
Acrylic latex

## TECHNICAL DATA SHEET

### DESCRIPTION

Our **Proline Eco 7050** is a Zero VOC acrylic latex ceiling flat finish paint for indoor use. It can be applied directly onto porous surfaces without requiring a primer. It is easy to apply, without spattering and dries quickly. It was developed to answer the needs of professional painters. The **Proline Eco 7050** can be used for commercial, industrial and residential projects.

USE	LIMITATIONS
This paint is applicable on interior surfaces. <b>Proline Eco 7050</b> is self-priming and can be applied directly onto porous surfaces that haven't been primed. It is recommended for drywall, concrete, masonry and wood. It must be applied on well prepared metal surfaces.	Avoid application in all temperatures under 10°C Not for exterior use Do not use on flooring Wait 30 days before proceeding with the first cleaning

### CARACTERISTICS

- **Proline Eco 7035** is ideal for LEED projects or any other projects requiring Zero VOC paints.
- Approved MPI category #143
- It does not require the use of a primer sealer on new drywall.
- During the work, minimal protection is required for baseboards and flooring.

### TECHNICAL INFORMATION

<b>DRYING TIME</b>	Recoat:	To touch:
	4 hours	30 minutes
At 25° Celsius. Relative humidity at 50%.		
<b>SURFACE COVERAGE (for 3.78 L)</b>	33 - 42m <sup>2</sup> (350 - 4500 ft <sup>2</sup> ) May vary depending on the surface porosity	
<b>Recommended film thickness</b>	Wet : 3.6 - 4.6 mils Dry : 1.25 - 1.60 mils	
<b>Cleaning</b>	Lukewarm soapy water	
<b>Resin</b>	Acrylic latex	
<b>Thinner</b>	Water	
<b>Inflammability</b>	N/A	
<b>Flash point</b>	N/A	
<b>% of solids by weight</b>	50%	
<b>% of solids by volume</b>	35%	
<b>VOC</b>	Zero VOC	
<b>GLOSS Ceiling flat</b>	<b>60°</b> 2,0-3,0% <b>85°</b> 2,5-3,5% The value is measured based on the white. The value may vary according to the chosen colour.	

TINTING BASES		946 ml	3,78 L	18,9 L	
7050-8	Neutral white		X	X	max. of 2 oz of colorant/3,78 L paint.

### STANDARDS

<b>MPI</b>	Category #143 GPS-1, GPS-2
<b>ONGC</b>	Type 1GP 100
<b>CFIA</b>	Product approved

SURFACE PREPARATION	RECOMMENDED PRIMER
<p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p><b>Presence of mold:</b> Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> <p><b>Flaking or peeling paint:</b> Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth.</p> <p>A repair compound should be used to fill holes and uneven surfaces. Sand with a grit #100 sandpaper.</p> <p><b>New drywall :</b> To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.</p> <p><b>Concrete/Masonry:</b> Wait until the concrete and/or masonry has cured at least 30 days before painting it.</p> <p><b>Aluminum, galvanized metal, and interior ferrous metal:</b> Remove all traces of oxidation (rust), then clean with <b>Metal Plus 467</b>, metal conditioner.</p> <p><b>Wood:</b> The surface must be sanded with a grit #80 or #100 sandpaper to smoothen the surface.</p>	<p><b>Drywall:</b> Only 2 coats of <b>Proline Eco 7050</b> can be applied directly onto the surface or use <b>Proline 7065</b>.</p> <p><b>Concrete block/rough brick:</b> Only 2 coats of <b>Proline Eco 7050</b> can be applied directly onto the surface or apply the <b>Proline 6006</b> block filler to level the surface.</p> <p><b>New Concrete:</b> Apply the <b>Proline Eco 7050</b> directly onto the surface.</p> <p><b>New wood:</b> Only 2 coats of <b>Proline Eco 7050</b> can be applied directly onto the surface or use the <b>Portico 270</b>.</p> <p><b>Pine knots:</b> Seal the pine knots with the <b>Stop Plus 298</b>.</p> <p><b>Red cedar and redwood:</b> Apply one to two coats of <b>Block Plus 296</b> alkyd based.</p> <p><b>Aluminum, galvanized metal, and interior ferrous metal:</b> Apply a coat of <b>Adhero Plus 290</b>.</p> <p><b>Latex paint:</b> No primer is required.</p> <p><b>Alkyd paint:</b> Apply an undercoat of <b>Adhero Plus 290*</b>.</p> <p><b>Dark colours:</b> Some dark colours may require the application of a dark tinted primer in order to improve opacity. Use <b>Proline</b> products <b>6070-2</b> and <b>6070-4</b> or <b>Adhero Plus 290-2</b> and <b>290-4</b>, available in more than 30 colours.</p> <p><i>If the surface to be primed is not mentioned, please contact an MF Paints distributor for further recommendations.</i></p> <p><i>*See limitations for <b>Adhero Plus 290</b>.</i></p>
<p><b>APPLICATION</b></p> <p>This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colours and 8 hours for dark colours. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.</p> <p><b>For spray application :</b> Dilute with a maximum of 10% water.</p> <p><b>Pressure :</b> 2000 to 2500 lb/in<sup>2</sup>*</p> <p><b>Nozzle :</b> 0.017 – 0.021*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p>	<p><b>STORAGE</b></p> <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p> <p><b>MAINTENANCE</b></p> <p>Allow a 30 day drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface using a light, circular motion.</p>
<p><b>WARRANTY</b></p> <p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<p><b>CAUTION</b></p> <ul style="list-style-type: none"> <li>• Keep away from children's reach</li> <li>• Keep lid closed when not in use</li> <li>• Avoid freezing</li> </ul>

**" Contact your municipality to dispose of the container in an environmentally-friendly manner "**