



# TECHNICAL DATA SHEET



## 7065 SERIES

Primer Sealer  
Acrylic latex

### DESCRIPTION

Our **Proline Eco 7065** is a Zero VOC acrylic latex primer sealer for indoor use. **Proline Eco 7065** does not contain any volatile organic compounds that can contribute to air pollution. It is easy to apply and dries quickly. It is formulated to seal new drywall. It was developed to answer the needs of professional painters. The **Proline Eco 7065** can be used for commercial, industrial and residential projects.

USE	LIMITATIONS
This primer sealer is applicable on interior surfaces. It seals and hides repairs in order to obtain a uniform gloss once the topcoat is applied. <b>Proline Eco 7065</b> is recommended for new surfaces such as drywall, concrete, and wood.	Avoid application in all temperatures under 10°C Not for exterior use Do not use on flooring Do not apply on alkyd paint Do not apply on pearl or glossy surfaces May crack if overloaded in the corners

CARACTERISTICS	TECHNICAL INFORMATION					
<ul style="list-style-type: none"> <li>It is ideal for LEED projects or any other projects requiring Zero VOC primers.</li> <li><b>Proline Eco 7065</b> seals drywall and joint compound.</li> <li>It dries quickly and can be covered after only 3 hours.</li> <li>It provides good hiding.</li> <li><b>Proline Eco 7065</b> can easily be sanded after a 3 hour drying time without overloading the sandpaper.</li> </ul>	<table border="1"> <tr> <td rowspan="2"><b>DRYING TIME</b></td> <td>Recoat:</td> <td>To touch:</td> </tr> <tr> <td>4 hours</td> <td>30 minutes</td> </tr> </table>	<b>DRYING TIME</b>	Recoat:	To touch:	4 hours	30 minutes
<b>DRYING TIME</b>	Recoat:		To touch:			
	4 hours	30 minutes				
	At 25° Celsius Relative humidity at 50% May differ depending on the colour					
	<b>SURFACE COVERAGE (for 3.78 L)</b>	33 - 42 m <sup>2</sup> (350 - 450 ft <sup>2</sup> ) May vary depending on the surface				
	<b>Recommended film thickness</b>	Wet : 3.6 - 4.6 mils Dry : 1.28 - 1.65 mils				
	<b>Cleaning</b>	Lukewarm soapy water				
	<b>Resin</b>	Acrylic latex				
	<b>Thinner</b>	Water				
	<b>Inflammability</b>	N/A				
	<b>Flash point</b>	N/A				
	<b>% of solids by weight</b>	53%				
	<b>% of solids by volume</b>	36%				
	<b>VOC</b>	Zero VOC				
	<b>GLOSS</b>	60° N/A 85° N/A				

TINTING BASES				
		946 ml	3,78 L	18,9 L
7065-0	White		X	X

SURFACE PREPARATION	
<p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p><b>Presence of mold:</b> Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> <p><b>Flaking or peeling paint:</b> Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound should be used to fill holes and uneven surfaces. Sand with a grit #100 sandpaper.</p> <p><b>New drywall :</b> To avoid creating an undesirable texture on the drywall, the joint compound must not be sanded excessively.</p> <p><b>Concrete/Masonry:</b> Wait until the concrete and/or masonry has cured at least 30 days before painting it.</p> <p><b>Wood:</b> The surface must be sanded with a grit #80 or #100 sandpaper to smoothen the surface.</p>	
APPLICATION	MAINTENANCE
<p>This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.</p> <p><b>For spray application :</b> Dilute with a maximum of 10% water.</p> <p><b>Pressure :</b> 2000 to 2500 lb/in<sup>2</sup>*</p> <p><b>Nozzle :</b> 0.017 – 0.021*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p>	<p>Must be topcoated.</p>
	STORAGE
	<p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p>
WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> <li>• Keep away from children's reach</li> <li>• Keep lid closed when not in use</li> <li>• Avoid freezing</li> </ul>

**" Contact your municipality to dispose of the container in an environmentally-friendly manner "**