



# DRYFALL

# 757

Latex Acrylic

Flat

## TECHNICAL DATA SHEET

### DESCRIPTION

**Dryfall 757** is an acrylic latex paint , for indoor use. The **Dryfall 757** is easy to apply and dries quickly. Developed for spraying commercial and warehouse ceiling.

| USAGE   | LIMITATIONS   |
|---|---|
| This dryfall paint is applicable on interior surfaces. <b>Dryfall 757</b> must be applied to new or painted surfaces that have been well prepared. It is recommended for ceilings exceeding 15 feet made of galvanised metal or other metal structure. (view <b>LIMITATIONS</b> and <b>SURFACE PREPARATION</b> section) | Avoid application in all temperatures under 10°C<br>The height must be 18 feet and more for dark colours.<br>Will not protect against rust in a humid area<br>Depending on the height of the ceiling, it is preferable to cover the floor, when the relative humidity is higher than 50%. |

| CHARACTERISTICS  | TECHNICAL INFORMATION |                 |
|--|-----------------------|-----------------|
| <ul style="list-style-type: none"> <li>When applied at a height exceeding 15 feet, with a 50% humidity level, any dryfall paint particles that have fallen to the floor may be swept away with a broom or vacuumed. The height must be 18 feet and more for dark colours.</li> <li>This dryfall paint will prevent flash rust from appearing on the surface during the application.</li> </ul> | <b>DRYING TIME</b>    | Recoat:         |
|  |                       | To touch:       |
|  |                       | 2 hours         |
|  |                       | 15 - 30 minutes |

At 25° Celsius  
Relative humidity at 50%  
May differ depending on the colour

|                                      |   |
|--------------------------------------|---|
| <b>Surface Coverage (for 3.78 L)</b> | 56 m <sup>2</sup> (600 ft <sup>2</sup> ) for steel deck ceilings with ceiling joists<br>112 m <sup>2</sup> (1200 pi <sup>2</sup> ) for a flat ceiling |
| <b>Recommended film thickness</b>    | N/A   |
| <b>Cleaning</b>                      | Lukewarm soapy water  |
| <b>Resin</b>                         | Acrylic latex   |
| <b>Thinner</b>                       | Water   |
| <b>Inflammability</b>                | N/A   |
| <b>Flash Point</b>                   | N/A   |
| <b>% of solids by weight</b>         | 61%   |
| <b>% of solids by volume</b>         | 42%   |
| <b>VOC</b>                           | <100 g/L  |
| <b>GLOSS</b>                         | <b>60°</b> 2.0-3.0%   |
| <b>Flat</b>                          | <b>85°</b> 2.5-3.5%   |

| TINTING BASES |               |        |        |        |                                    |
|---------------|---------------|--------|--------|--------|------------------------------------|
|               |               | 946 ml | 3,78 L | 18,9 L |                                    |
| 757-8         | Neutral White |        |        | X      | max. of 2 oz of colorant / 3,78 L  |
| 757-4         | Base D        |        |        | X      | max. of 8 oz of colorant / 3,78 L  |
| 757-5         | Base A        |        |        | X      | max. of 12 oz of colorant / 3,78 L |

| STANDARDS  |                          |
|------------|--------------------------|
| <b>MPI</b> | Certified Category # 118 |

| <b>SURFACE PREPARATION</b>  |  |
|---|--|
| <p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p>            |  |
| <b>APPLICATION</b>  | <b>MAINTENANCE</b>   |
| <p>Mix well before use. It is important to keep the humidity level above 50%, in order to maintain the dryfall properties at 15 feet.</p> <p><b>For spray application</b><br/> <b>Pressure :</b> 2000 at 2500 lb/po<sup>2</sup>*<br/> <b>Nozzle :</b> 0.015 – 0.019*</p> <p>*This data may vary depending on the brand of the equipment manufacturer.</p> | <p>N/A</p>   |
|   | <b>STORAGE</b>   |
|   | <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p> |

| <b>WARRANTY</b>  | <b>CAUTION</b>   |
|--|--|
| <p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p> | <ul style="list-style-type: none"> <li>• Keep away from children's reach</li> <li>• Keep lid closed when not in use</li> <li>• Avoid freezing</li> </ul> |

***" Contact your municipality to dispose of the container in an environmentally-friendly manner "***