

DESCRIPTION

Alkyd Plus 1320 is a high-quality alkyd-based paint, specially made to seal and adhere to calcimine surfaces. For interior and exterior use.

USE

This paints excellent adhesion properties allow for it to be easily applied on glossy or calcimine surfaces. Thanks to its concealing power, this paint hides colored surfaces and water rings.

ADVANTAGES

- For interior or exterior use
- Can be used on bare and painted surfaces.
- Recommended for calcimine surfaces on which a flat finish is required.
- Outdoors, it can be used on sidings, fences, terraces, patios and wood furniture.

LIMITATIONS

- Do not apply if temperature is below 10°C
- Do not apply under direct sunlight.

TECHNICAL DATA

| | | | |
|-------------------------|-----|----------------|------------|
| Resin | | Alkyd | |
| Color | | White | |
| Dilution | | N/A | |
| Tool cleaning | | Mineral spirit | MF-SOL 450 |
| Flash Point | | 42 | °C |
| Inflammability | | yes | |
| Solids by weight | | 72 | % |
| Solids by volume | | 51 | % |
| VOC | | <400 | g/l |
| Gloss | 60° | 2,5 | % |
| Sheen | 80° | 3 | % |

APPLICATION DATA

| | | | |
|--|---------------------------|---|--------|
| At 25° Celsius | | | |
| Relative humidity at 50% | | | |
| May differ depending on the colour | | | |
| Spreading Rate | | (36-42) m ² (400-450)sqft | gallon |
| May vary depending on the surface porosity | | | |
| Film Thickness | Wet | 3,56-4,01 | mils |
| | Dry | 1,82-2,05 | mils |
| Drying Time | Tack free | 8 | hours |
| | Recoat | 12-24 | hours |
| | Cleaning | 30 | days |
| Application | Brush | √ | |
| | Roller | 10 | mm |
| | Spray (Buse 0,015-0,019)* | 2000-2500 | lb/po2 |
| *This data may vary depending on the equipment of a manufacturer | | | |
| Exterior condition for application | | | |
| At least, no rain expected following application | | 24 | hours |
| Storage | Temperature | 10 et 30 | °C |
| Base | Formats | | |
| | 946ml | 3,78L | 18,9L |
| 1320-0 Super White | √ | √ | √ |



ALKYD

Plus

1320 Series

Calcimine surfaces

Alkyd

Flat Finish

TECHNICAL DATA SHEET

Interior/Exterior

SURFACE PREPARATION

The surface must be dry and clean, without traces of flaking, oil, grease, soap, wax, rust and dust. On painted surfaces, it is recommended to clean with T.S.P. (trisodium phosphate) to eliminate any contaminant that might harm the adhesion or the hardening of the product. Glossy surfaces must be sanded and dusted before painting. If the calcimine product is textured, you must scrub the surface with a broom to remove the fragile elements.

Mildew & new surfaces

On new or treated wood, having been exposed to inclement weather, it is highly recommended to neutralise all mildew, visible or not, to avoid peeling. Use a mix of 3 parts water for 1 part bleach, let this work for 20 minutes, then rinse and allow the wood to dry for at least 24 hours before painting. Once the surface is dry, sand the horizontal surface entirely with a n°80 sandpaper to open the wood fibers and enhance the adhesion. Use a n°120 sandpaper for vertical surfaces. Should a pressure wash be required, it must be done prior to sanding.

APPLICATION

Stir thoroughly before use. Apply one or two coats as required. Let dry at least 12 hours between each coat. A 10mm anti-felting roller or a quality bristle brush is recommended to enhance its application. For a spray application, dilute with a maximum of 10% mineral essence MF-SOL 450. Clean brushes and rollers with mineral essence.

WARRANTY

This product will give complete satisfaction if applied according to the manufacturer's instructions. In the event that this is found to be defective after inspection, the manufacturer's liability is limited to replacement of the product and does not include labor during application.

CAUTION

- Keep away from children.
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

**CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER
IN AN ENVIRONMENTALLY FRIENDLY MANNER**