

PLAYGROUND PAINT

Interior/Exterior

197 ACRYLIC VINYL BLUE

DESCRIPTION

Blue water-based paint for marking playgrounds.

Use

This paint is specially designed for marking playgrounds. This paint can be used on grass, asphalt and concrete and sand.

ADVANTAGES

- Good contrasting visibility
- > Sustainability
- Low VOC
- Easy application
- Easy cleaning of tools

LIMITATIONS

- > Avoid applications below 10°C
- Not used for road signs

SURFACE PREPARATION

The surface must be dry and clean, free of dust, oil, grease, rust and soap.

RECOMMENDED PRIMER

No primer required.

TECHNICAL DATA

Resin		Acrylic Vinyl			
Color		Blue			
Solvent		Water			
Flash Point		N/A			
Inflammability		N/A			
Solids by weight		26	%		
Solids by volume		15	%		
VOC		<100	g/l		
Gloss	60°	N/A	%		
Sheen	85°	N/A	%		
The value is measured from the white. It may vary depending on the color					

APPLICATION DATA

*At 25° Celsius								
Relative humidity at 50%								
May differ depending on the colour								
Spread rate in line	ear feet at 4 in							
and 5 mils wet thi	ckness	960 sqft	18,9L					
May vary depending on the	e surface porosity							
Drying Time*	Tack free	Tack free			min			
	Recoat	Recoat			hours			
Application	Brush	Brush		V				
	Roller	Roller			mm			
	Spray Airle	Spray Airless (Nozzle(0,015-0,019)**			lb/sqin			
**This data may vary depending on the equipment of a manufacturer								
Exterior application and condition				N/A				
Storage	Temperati	Temperature between			°C			
Tinted Based Format								
	946ML	3,78L	18,9L					
197-0 Blue			V					



PLAYGROUND PAINT

Interior/Exterior

APPLICATION

Stir thoroughly before application. Should the paint be too thick when it's applied with a spray gun, it is recommended to dilute with a maximum of 10% water.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

The paint will then dry to a whiter finish.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- > Keep away from children's reach
- > Keep in a dry area between 10° C-30° C
- > Keep lid closed when not used.
- > Avoid freezing.

DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER