

### DESCRIPTION

Yellow water-based paint for marking playgrounds.

### USE

This paint is specially designed for marking playgrounds. This paint can be used on grass, asphalt and concrete and sand.

### ADVANTAGES

- Good contrasting visibility
- Sustainability
- Low VOC
- Easy application
- Easy cleaning of tools

### LIMITATIONS

- Avoid applications below 10°C
- Not used for road signs

### SURFACE PREPARATION

The surface must be dry and clean, free of dust, oil, grease, rust and soap.

### RECOMMENDED PRIMER

No primer required.

### TECHNICAL DATA

<b>Resin</b>	Acrylic Vinyl		
<b>Color</b>	Yellow		
<b>Solvent</b>	Water		
<b>Flash Point</b>	N/A		
<b>Inflammability</b>	N/A		
<b>Solids by weight</b>	28		%
<b>Solids by volume</b>	16		%
<b>VOC</b>	<25		g/l
<b>Gloss</b>	60°	N/A	%
<b>Sheen</b>	85°	N/A	%

The value is measured from the white. It may vary depending on the color

### APPLICATION DATA

*At 25° Celsius			
Relative humidity at 50%			
May differ depending on the colour			
<b>Spread rate in linear feet at 4 inches wide and 5 mils wet thickness</b>		960 sqft	18,9L
May vary depending on the surface porosity			
<b>Drying Time*</b>	Tack free	30	min
	Recoat	30-60	hours
<b>Application</b>	Brush	√	
	Roller	10	mm
	Spray Airless (Nozzle(0,015-0,019)**	2000-2500	lb/sqin
**This data may vary depending on the equipment of a manufacturer			
<b>Exterior application and condition</b>		N/A	
<b>Storage</b>	Temperature between	10 et 30	°C
<b>Tinted Based</b>	<b>Format</b>		
	946ML	3,78L	18,9L
198-0 Yellow			√

### APPLICATION

Stir thoroughly before application. Should the paint be too thick when it's applied with a spray gun, it is recommended to dilute with a maximum of 10% water.

According to the required pigmentation by the applicator, an additional dilution could be made while keeping in mind that a higher dilution may cause the paint to fade quicker after a rainfall, and can dry to be paler.

The paint will then dry to a whiter finish.

### WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

### CAUTION

- Keep away from children's reach
- Keep in a dry area between 10° C-30° C
- Keep lid closed when not used.
- Avoid freezing.

***DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER***