

### DESCRIPTION

ISO-TEX 205 series is a decorative textured coating based on latex emulsion and granules from volcanic rocks.

### USE

ISO-TEX can be used inside and outside (under certain conditions see Limitations). Designed specifically for home foundations and ceilings. Suitable for both commercial and institutional residential project.

### ADVANTAGES

- Its strong consistency makes it possible to fill the cavities of irregular surfaces.
- When dry, it gives a rich, grainy finish.
- Rustic appearance
- Ecological
- This coating contains a low level of VOCs

### LIMITATIONS

- Avoid application at temperatures below 10°C or in direct sunlight.
- Do not apply on the floor.
- Must be topcoated for exterior applications (See Recommended Finish)

### TECHNICAL DATA

<b>Resin</b>	Latex Acrylic and granule	
<b>Color</b>	White	
<b>Solvent</b>	Water	
<b>Flash Point</b>	N/A	
<b>Inflammability</b>	N/A	
<b>Solids by weight</b>	73	%
<b>Solids by volume</b>	58	%
<b>VOC</b>	<50	g/l
<b>Gloss</b>	60°	N/A %
<b>Sheen</b>	85°	N/A %
<b>Standards</b>	Type 1GP 162	

### APPLICATION DATA

*At 25° Celsius			
Relative humidity at 50%			
May differ depending on the colour			
<b>Spreading Rate</b>		4,8-9,6 m <sup>2</sup>	
	May vary depending on the surface porosity	(500-100sqft)	gallon
<b>Film Thickness</b>	Wet	16-32	mils
	Dry	9,3-18,6	mils
<b>Drying Time*</b>	Tack free	1	hour
	Recoat	2-4	hours
	Cleaning	30	days
<b>Application</b>	Trowel	√	
	Roller	Textured	
	Spray Airless	N/A	lb/sqin
<b>Exterior application and condition</b>		N/A	
<b>Storage</b>	Temperature between	10 et 30	°C
<b>Base</b>	<b>Format</b>		
	946ML	3,78L	18,9L
205-0 White		√	√



### SURFACE PREPARATION

The surface must be dry and clean, free of dust, oil, grease, rust, and soap. On a previously painted surface, it is recommended to wash with a degreaser (TSP) to remove any contaminants that may affect the adhesion and hardening of the product. Shiny surfaces MUST be well sanded and dusted.

### RECOMMENDED PRIMERS

**Drywall or masonry:** Apply Latex Plus 170 primer sealer.

**Exterior masonry:** Apply Portico 270 undercoat before finishing.

**Ferrous metal:** Apply an ISO-RUST 4350 or 4370 anti-rust primer.

**Latex paint:** No primer required.

**Glossy alkyd paint:** Apply Adhéro Plus 290 undercoat.

### RECOMMEND FINISH

If applied outside, the ISO-TEX must be top coated with 2 coats of Atmosphere exterior paint 2268 matte or 2260 Satin. For interior application no restriction is needed.

### APPLICATION

Mix well before use. Apply evenly using a trowel and a textured roller and be sure to always complete the last strokes of the roller in the same direction. Even out the texture perfectly, if necessary, by re-rolling the already covered and undried surface without adding ISO-TEX.

### WARRANTY

This product will give complete satisfaction if applied according to the manufacturer's instructions. In the event that this is found to be defective after inspection, the manufacturer's liability is limited to replacement of the product and does not include labor during application.

### CAUTION

- Keep out of the reach of children
- Keep container closed when not in use
- Avoid freezing

**CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER.**