



Premium

370

Primer Sealer Latex Acrylic

INTERIOR

TECHNICAL DATA SHEET

DESCRIPTION

Premium 370-0 is an acrylic latex primer sealer, formulated to seal new drywall.

Easy to apply, it provides a uniform topcoat and optimises the hiding of the finish. Can be used for residential and institutional projects.

USE

This interior primer seals drywall joint, and plaster repair. can be also used on new surfaces such as concrete, and wood.

(See limitations and recommended primer).

ADVANTAGES

- Easy to apply.
- Low VOC content
- Excellent sealer for new drywall
- Can be sanded after 3 hours.
- Allows uniform finish.

LIMITATIONS

- Avoid application at temperatures below 10 ° C
- Do not use on floors.
- Do not mix with other paints.
- Do not apply on alkyd paint.
- Not designed to seal wood that can bleed.
- Do not apply on glossy surfaces.
- Can crack if over thick in the corners.

TECHNICAL DATA

Resin	Latex Acrylic		
Color	White		
Solvent	Water		
Cleaning tools	Water		
Flash Point	N/A		
Inflammability	N/A		
Solids by weight	47	%	
Solids by volume	30	%	
VOC	<50	g/l	
Gloss	60°	N/A	
Sheen	80°	N/A	
Standards	GCSB Type IGP 119		

APPLICATION DATA

At 25° Celsius			
Relative humidity at 50%			
May differ depending on the colour			
Spreading Rate	33-42 m ²		gallon
May vary depending on the surface porosity		(350-450sqft)	
Film Thickness	Wet	3,5-4,5	mils
	Dry	1,05-1,35	mils
Drying Time	Tack free	30	min
	Recoat	3	hours
	Cleaning	N/A	
Application	Brush	√	
	Roller	15	mm
	Spray (Nozzle 0,015-0,019)*	2000-2500	lb/po2
*This data may vary depending on the equipment of a manufacturer			
Exterior application and conditions	N/A		
Base	Formats		
	946ml	3,78L	18,9L
370-0 white		√	√



Premium

370

Primer Sealer
Latex Acrylic

TECHNICAL DATA SHEET

INTERIOR

SURFACE PREPARATION

The surface should be dry and clean, free from dust, oil, grease, rust and soap. On painted surface, it is recommended to clean with a degreaser (TSP) in order to remove any contaminant that could interfere with the adhesion and/or the full cure of the product. Rinse the entire surface thoroughly. Surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts of water. Rinse with clean water before it dries the entire surface thoroughly and let it dry.

Flaking or peeling: Remove mechanically the weakened paint, then sand the surface to make it even. A repair compound should be used to fill holes and uneven surfaces. Sand with # 150 grit sandpaper.

New Drywall: To avoid creating an unwanted texture on the drywall sheet, joint compound should not be sanded excessively.

Concrete / Masonry: Allow concrete / masonry to cure at least 30 days before painting.

Wood without bleeding: The surface should be sanded with # 80 or # 100 grit sandpaper to improve adhesion.

APPLICATION

Mix well before use. Apply a coat or two if needed. Let dry at least 3 hours or more. To hide the surface well, it is recommended to use a roller of at least 15mm anti-felt and a quality nylon-polyester brush. For spray application, dilute with a maximum of 10% water. Wash rollers and brushes in warm soapy water.

For spray application: Maybe diluted with a maximum of 10% water.

Pressure: 2000 to 2500 lb/sqin*

Nozzle: 0.015 – 0.019

*This data may vary depending on the brand of the equipment manufacturer

MAINTENANCE

Must be topcoated

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN
AN ENVIRONMENTALLY-FRIENDLY MANNER