

DESCRIPTION

Selection 5371 is an acrylic latex primer sealer, designed for interior application. This primer is easy to apply, no spattering and dries quickly. Selection 5371 can be used for maintenance of residential projects.

USE

Selection 5371 should be applied to properly prepared surfaces. It is suitable for new or previously painted surfaces. It is recommended for drywall.

ADVANTAGES

- Can be sanded after 4 hours
- Easy to apply
- Controlled spattering
- Good leveling
- Low VOC

LIMITATIONS

- Avoid application at temperatures below 10 ° C
- Do not use on floors
- Do not mix with other paints
- Not designed to seal surfaces with bleeding

TECHNICAL DATA

Resin	Latex Acrylic		
Color	White		
Solvent	Water		
Flash Point	N/A		
Inflammability	N/A		
Solids by weight	49	%	
Solids by volume	32	%	
VOC	<50	g/l	
Gloss	60°	N/A	%
Sheen	85°	N/A	%
Standards	N/A		

APPLICATION DATA

*At 25° Celsius			
Relative humidity at 50%			
May differ depending on the colour			
Spreading Rate		35-42 m ²	
	May vary depending on the surface porosity	(375-450sqft)	gallon
Film Thickness	Wet	3,6-4,3	mils
	Dry	1,14-1,37	mils
Drying Time*	Tack free	30	min
	Recoat	4	hours
	Cleaning	N/A	days
	Final cure	30	days
Application	Brush	√	
	Roller	10	mm
	Spray Airless (Nozzle(0,015-0,019)*)	2000-2500	lb/sqin
*This data may vary depending on the equipment of a manufacturer			
Exterior application and condition		N/A	
Storage	Temperature between	10 et 30	°C
Tinted Based	Format		
	946ML	3,78L	18,9L
5371- 0 White	√	√	



Selection

5371

Primer Sealer
Latex Acrylic

TECHNICAL DATA SHEET

INTERIOR

SURFACE PREPARATION

The surface should be dry and clean, free from dust, oil, grease, rust and soap. On painted surface, it is recommended to clean with a degreaser (TSP) in order to remove any contaminant that could interfere with the adhesion and/or the full cure of the product. Rinse the entire surface thoroughly. Surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts of water. Rinse before it dries the entire surface thoroughly and let it dry.

Flaking or peeling: Using a scraper, remove weakened paint, then sand the edges of the surface to make it smooth. A repair compound should be used to fill holes and uneven surfaces. Sand with # 150 grit sandpaper.

Glossy latex paint: Sand with # 150 grade sandpaper, then dust the surface.

New Drywall: To avoid creating an unwanted texture on the drywall sheet, joint compound should not be sanded excessively.

APPLICATION

This product is ready to use and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow 4 hours drying time. In order to properly cover the surface, it is recommended to use a 10 mm lint free roller and a quality nylon-polyester brush. Clean rollers and brushes with warm soapy water after using them.

For spray application: Maybe diluted with a maximum of 10% water.

Pressure: 2000 to 2500 lb/sqin*

Nozzle: 0.015 – 0.019*

*This data may vary depending on the brand of the equipment manufacturer

MAINTENANCE

Must be recoated.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN
AN ENVIRONMENTALLY-FRIENDLY MANNER