

SAFETY DATA SHEET (SDS)

Section 1. Identification				
Product identifier	4055-0			
Other means of identification ISO-RUST, Rust resistant paint, aluminum				
Recommended use and restrictions on use For metal surfaces				
Initial supplier identifier MF Paints Inc. 1605 Dagenais Boulevard W, Laval, QC H7L 5A3 T:(450) 628-3831				
Emergency telephone number/restriction on use			e Canada – CANUTEC 24 hour number 613-996-6666	

Section 2. Hazard identification Classification of hazardous product (name of the category or subcategory of the hazard class)

Flammable liquid (Category 3)

Skin irritation (Category 2)

Eye irritation (Category 2A)

Specific target organ toxicity – single exposure (Category 3), Central nervous system

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)





Danger

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bound container and receiving equipment. P241 Use explosion-proof equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P302 + P352 IF ON SKIN: wash with plenty of water. P332 + P313 IF SKIN irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P370 + P378 In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish. P403 + P233 + P235 Store in a well-ventilated place. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known None					
Section 3. Composition/information on ingredients					
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*			
Medium aliphatic solvent naphtha	64742-88-7	< 10			
Aluminum, powder	7429-90-5	< 15			
Petroleum distillates C4-C12	64742-49-0	< 30			
Aromatic petroleum distillates	64742-95-6	< 5			
1,2,4-Trimethylbenzene	95-63-6	< 5			
Kerosene	64742-47-8	< 5			
Stoddard solvent	8052-41-3	< 10			
Xylene	1330-20-7	< 1			
Ethyl benzene	100-41-4	< 1			
* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).					



Section 4. First-aid measures				
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.			
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is			
	rapidly losing consciousness, or is unconscious or	convulsing. Rinse mouth thoroughly with water. Have victim drink two		
	glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.			
Skin contact	IF ON SKIN: wash with plenty of water. (15-20 minutes). IF SKIN irritation or rash occurs: Get medical attention. Take off			
	contaminated clothing and wash it before reuse.			
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue			
-	rinsing. If eye irritation persists: Get medical attention.			
Most important symptoms and effects (acute or delayed)		Causes skin irritation. Causes serious eye irritation.		
Indication of immediate medical attention/special treatment		In all cases, call a doctor. Do not forget this document.		
Section 5. Fire-fighting measures				
Specific bazards of the bazardous product (bazardous combustion products)				

Specific hazards of the hazardous product (hazardous combustion products

Carbon oxides and other irritant/toxic gases and fumes.

Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Section 7. Handling and storage

Precautions for safe handling

Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: DUST ACGIH - TLV-TWA 1 mg/m³ & PEL-TWA 5 mg/m³ (respirable fraction) & 15 mg/m³ (total dust); CAS 8052-41-3 ACGIH - TLV-TWA 100 ppm & PEL-TWA 500 ppm; CAS 1330-20-7 ACGIH - TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 95-63-6 ACGIH - TLV-TWA 25 ppm; CAS 100-41-4 ACGIH - TLV-TWA 20 ppm & PEL-TWA 100 ppm;

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.



Section 9. Physical and chemical properties						
Appearance, physical state/colour Liquid	Vapour pressure Not available					
Odour Characteristic	Vapour density Not available					
Odour threshold Not available	Relative density 0.974 g/L					
pH Not available	Solubility Not available					
Melting/freezing point Not available	Partition coefficient - n-octanol/water Not available					
Initial boiling point/range Not available	Auto-ignition temperature Not available					
Flash point 28°C closed cup	Decomposition temperature Not available					
Evaporation rate Not available	Viscosity 66 cSt @ 40°C					
Flammability (solids and gases) Not available	VOC Not available					
Upper and lower flammability/explosive limits Not available	Other None known					
Section 10. Stability and reactivity						

Reactivity

Does not react under the recommended storage and handling conditions prescribed.

Chemical stability

Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

Incompatible materials

Oxidizing materials; etc.

Hazardous decomposition products

None known

Section 11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization - No data available; Respiratory Sensitization - No data available; Germ Cell Mutagenicity - No data available; Carcinogenicity - No ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity - No data available; Specific Target Organ Toxicity - Single Exposure - Possible; Specific Target Organ Toxicity - Repeated Exposure - No data available; Aspiration Hazard - No data available; Health Hazards Not Otherwise Classified - No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)

CAS 1330-20-7 Oral, rat LD₅₀ 4300 mg/kg; Dermal, rabbit LD₅₀ 12100 mg/kg; CAS 64742-95-6 Oral, rat LD₅₀ 8400 mg/kg; CAS 100-41-4 Oral, rat LD₅₀ 3500 mg/kg; Dermal, rabbit LD₅₀ 15380 mg/kg;

ATE not available in this document.

Section 12. Ecological information

Ecotoxicity (aquatic and terrestrial information) No data available for the product.

Persistence and degradability No data available

Bioaccumulative potential No data available

Mobility in soil No data available

Other adverse effects No data available

Section 13. Disposal considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG III

Special precautions (transport/conveyance) May also be shipped as a LIMITED QUANTITY in accordance with TDG.

Environmental hazards (IMDG or other) None

Bulk transport (usually more than 450 L in capacity) Possible



Section 15. Regulatory information				
Safety/health Canadian regulations spec	ifics Refer to Section 2 for the appropriate classification. This product has been classified in accordance			
	with the hazard criteria of the Hazardous Products Regulations (HPR).			
Environmental Canadian regulations sp	ecifics Refer to Section 3 for ingredient(s) of the DSL			
Safety/health/environmental outside regulations specifics				
United States OSHA information: This product is regulated according to OSHA (29 CFR).				
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.				
United States TCSA information: Refer to the ingredients listed in Section 3.				
California Proposition 65: This product may contain traces of ingredient known to the State of California to cause cancer or other reproductive harm.				
	Section 16. Other information			
Date of the latest revision of the safety d	ata sheet August 14, 2018 version 1 (NSS ENTREPRISE INC.)			
References Safety Data Sheets from	manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.			
Abbreviations				
ACGIH American Conference of	Governmental Industrial Hygienists			
ATE Acute toxicity estimate	Acute toxicity estimate			
	Chemical Abstract Service			
	Domestic Substance List			
	International Agency for Research on Cancer			
	International Air Transport Association			
	International Maritime Dangerous Goods Code			
	Lethal concentration			
S .	Lethal Dosage			
	National Institute for Occupational Safety and Health			
	National Toxicology Program (U.S.A.)			
	Occupational Safety and Health Administration (U.S.A.)			
1	Permissible Exposure Limit			
	Short-term Exposure Limit			
	Transport of dangerous goods in Canada			
	Threshold Limit Value			
TWA Time Weighted Average	Toxic Substances Control Act			
	Workplace Hazardous Materials Information System			
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability				

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.