



DESCRIPTION

Floor Paint 3500 platinum finish is a 100% acrylic urethane fortified paint, of superior quality for indoor and outdoor floors. It is easy to apply, without spattering and dries quickly. It can be used for commercial, institutional and residential projects. **Do not use on floors subject to be in contact with tires.**

USE	LIMITATIONS
<p>This paint is applicable on interior and exterior floors. Floor Paint 3500 must be applied to floors that have been well prepared and properly primed. It is recommended for solid wood, plywood or fiberglass floors, for new cement floors of at least 28 days and any floors that have been painted or stained with latex or alkyd paint.</p> <p>Areas: Basement, deck, balcony, steps, porch...</p>	<p>Avoid application in all temperatures under 10°C</p> <p>Do not apply under direct sunlight</p> <p>Do not apply directly on ferrous metals (iron, steel)</p> <p>Do not use on floors with intense commercial traffic</p> <p>Do not use on floors that have direct contact with tires</p> <p>Do not mix with other types of paint.</p> <p>Wait 15 days before proceeding with the first cleaning</p> <p>An intense traffic, a high humidity level and a lack of wood aeration can result in a paint film failure and a shorter durability.</p> <p>If alkyd paint is present, clean the floor properly and sand using a #60 -#80 grit sandpaper</p> <p>Wait 24 hours before circulating on the floor.</p>

CHARACTERISTICS		TECHNICAL INFORMATION													
<ul style="list-style-type: none"> • Floor Paint 3500 clings to well-prepared surfaces without the need for a primer (view SURFACE PREPARATION and RECOMMENDED PRIMER sections). • It is waterproof while letting the surface breathe. • Offers resistance to concrete alkalinity. • Good resistance to common cleaners, wear, salt, oil, water and weak acids stains. • Easy to maintain. • Offers a good resistance to weathering, crackling, peeling and flaking. • Resists to yellowing, chalking and discoloration. • All the tools are easily washable with soapy lukewarm water. • Offers an excellent flexibility as well as a good resistance against humidity. • It reaches its full cure only 14 days after application. 		<table border="1"> <tr> <td rowspan="2">DRYING TIME</td> <td>Recoat:</td> <td>To touch:</td> <td colspan="2">Exterior:</td> </tr> <tr> <td>4-6 hours</td> <td>20 to 30 minutes</td> <td colspan="2">Plan for dry weather 4 hours after application</td> </tr> </table>	DRYING TIME	Recoat:	To touch:	Exterior:		4-6 hours	20 to 30 minutes	Plan for dry weather 4 hours after application		<p>At 25° Celsius</p> <p>Relative humidity at 50%</p> <p>May differ depending on the colour</p>			
DRYING TIME	Recoat:			To touch:	Exterior:										
	4-6 hours	20 to 30 minutes	Plan for dry weather 4 hours after application												
		SURFACE COVERAGE (for 3.78 L)	42 - 51 m ² (450 - 550 ft ²)												
		Recommended film thickness	Wet : 2.9 - 3.55 mils Dry : 0.97 - 1.17 mils												
		Cleaning	Lukewarm soapy water												
		Resin	100% acrylic, Polyurethane												
		Thinner	Water												
		Inflammability	N/A												
		Flash point	N/A												
		% of solids by weight	44%												
		% of solids by volume	33%												
		VOC	<100 g/L												
		GLOSS	60° 20 - 30%												
		Platinum	85° 60 - 70%												
			The value is measured based on the white.												
			The value may vary according to the chosen colour.												
TINTING BASES															
		946 ml	3,78 L	18,9 L											
3500-0	White	X	X												
3500-1	P Base	X	X		max. of 2 oz of colorant / 3,78 L										
3500-2	M Base	X	X		max. of 5 oz of colorant / 3,78 L										
3500-4	D Base	X	X		max. of 8 oz of colorant / 3,78 L										
3500-5	A Base	X	X		max. of 12 oz of colorant / 3,78 L										
COLOURS															
3573-0	Grey	X	X	X											

SURFACE PREPARATION	RECOMMENDED PRIMER	
<p>The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may harm the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.</p> <p>Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.</p> <p>Flaking or peeling paint: Using a scraper, remove the weakened and/or loose paint, then sand the edges of the surface to make it smooth. A repair compound must be used to fill holes and uneven surfaces. Sand with a #80 grit sandpaper.</p> <p>Concrete: Wait until the concrete has cured at least 28 days before painting it. Old concrete must be cleaned with a solution of muriatic acid and water, then rinsed with clean water. Make sure there is no hydrostatic pressure from the floor and that the humidity does not exceed 5%.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Remove all traces of oxidation (rust), then clean with Metal Plus 467, metal conditioner.</p> <p>New or treated wood having been exposed to bad weather: It is strongly recommended that any apparent or undesirable mold growth be neutralized in order to prevent peeling. Use a mixture of 1 part bleach to 3 parts water, let stand for 20 minutes to take effect, then rinse and allow the wood to dry for at least 24 hours.</p> <p>Wood: The surface must be sanded with a #80 or #100 grit sandpaper to smoothen the surface. Remove the resin present on the knots and the veins of the wood with a paint thinner.</p> <p>Alkyd paint: It is important to sand the surface well. Remove the dust created during sanding. Repair holes and cracks with a suitable repair compound.</p> <p>Fiberglass: It is important to clean the surface with acetone.</p>	<p>Concrete blocks/rough brick: Apply the Proline 6006 block filler to level the surface or apply Floor Paint 3500 directly.</p> <p>New Concrete: Apply Floor Paint 3500 directly onto the surface.</p> <p>New wood: Apply Floor Paint 3500 directly onto the surface.</p> <p>Pine knots: Seal the pine knots with the Stop Plus 298.</p> <p>Red cedar and redwood: Apply one to two coats of Block Plus 296 alkyd based.</p> <p>Aluminum, galvanized metal, and interior ferrous metal: Apply a coat of Adhero Plus 290 or Adhero Hybrid 297.</p> <p>Exterior ferrous metal: ISO-RUST 4350 or 4370</p> <p>Latex paint: Apply Floor Paint 3500 directly onto the surface.</p> <p>Alkyd paint: Apply Floor Paint 3500 directly onto the surface.</p> <p>Fiberglass: Apply Floor Paint 3500 directly onto the surface.</p> <p><i>If the surface to be primed is not mentioned, please contact an MF Paints distributor for further recommendations.</i></p>	
APPLICATION	MAINTENANCE	
<p>This product is ready to be used and does not require dilution. Mix well before use. For a better durability apply 3 coats of paint. Allow a minimum drying time of 4 hours between each coat for pale colours and 8 hours for dark colours. In order to properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.</p> <p>Anti-Skid: Add to the paint 1 lb of aggregate / gallon, (half the container) MFHWS for the first coat. Then apply the second coat without the aggregate, as it is. By doing so, the floor will be anti-skid and easy to maintain. Make sure to mix the paint regularly with the aggregate to maintain good mixing uniformity</p> <p>Stage Floor: See your MF Paints representative.</p> <p>For spray application : Dilute with a maximum of 10% water.</p> <p>Pressure : 1500 to 2000 lb/in²*</p> <p>Nozzle : 0.015 – 0.021*</p> <p><i>*This data may vary depending on the brand of the equipment manufacturer.</i></p>	<p>Allow a 14 day drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface using a light, circular motion. If the surface is damaged, touch up these areas and apply a coat of paint over the entire surface.</p> <th data-bbox="865 1283 1567 1325">STORAGE</th> <p>Store the paint in a dry area and maintain temperature between 10°C and 30°C.</p>	STORAGE

WARRANTY	CAUTION
<p>This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.</p>	<ul style="list-style-type: none"> • Keep away from children's reach • Keep lid closed when not in use • Avoid freezing

" Contact your municipality to dispose of the container in an environmentally-friendly manner "