



# Selection

## 5336

### Ceiling Flat Latex Acrylic

TECHNICAL DATA SHEET

INTERIOR

#### DESCRIPTION

**Selection 5336** is an acrylic latex paint flat finish, designed for interior ceiling application. This paint is easy to apply, no spattering and dries quickly. Selection 5336 can be used for maintenance of residential projects.

#### USE

Selection 5336 should be applied to properly prepared and primed surfaces. It is recommended to be used to keep ceiling surfaces in good condition previously painted or primed.

#### ADVANTAGES

- Can be sanded after 4 hours
- Easy to apply
- Controlled spattering
- Good leveling

#### LIMITATIONS

- Avoid application at temperatures below 10 ° C
- Do not use on floors
- Do not mix with other paints
- Avoid frequent and aggressive cleaning
- Not designed to seal new wood that may bleed such as: (cedar, redwood, plywood, recomposed and glued wood, exotic wood or any other wood with bleeding) (see Recommended Primers)

#### TECHNICAL DATA

<b>Resin</b>	Latex Acrylic		
<b>Color</b>	White		
<b>Solvent</b>	Water		
<b>Flash Point</b>	N/A		
<b>Inflammability</b>	N/A		
<b>Solids by weight</b>	46	%	
<b>Solids by volume</b>	30	%	
<b>VOC</b>	<100	g/l	
<b>Gloss</b>	60°	1,5-2,0	%
<b>Sheen</b>	85°	1,5-2,0	%
<small>The value is measured from the white. It may vary depending on the color</small>			
<b>Standards</b>	<b>CGSB</b>	Type 1GP 100, 1GP 209	

#### APPLICATION DATA

<small>*At 25° Celsius</small>			
<small>Relative humidity at 50%</small>			
<small>May differ depending on the colour</small>			
<b>Spreading Rate</b>		28-37 m <sup>2</sup> (300-400sqft)	gallon
<small>May vary depending on the surface porosity</small>			
<b>Film Thickness</b>	Wet	4,0-5,3	mils
	Dry	1,08-1,44	mils
<b>Drying Time*</b>	Tack free	30	min
	Recoat	4	hours
	Cleaning	N/A	days
	Final cure	30	days
<b>Application</b>	Brush	√	
	Roller	15	mm
	Spray Airless (Nozzle(0,015-0,019)*)	2000-2500	lb/sqin
<small>*This data may vary depending on the equipment of a manufacturer</small>			
<b>Exterior application and condition</b>		N/A	
<b>Storage</b>	Temperature between	10 et 30	°C
<b>Tinted Based</b>	<b>Format</b>		
	946ML	3,78L	18,9L
5336-0 White	√	√	



# Selection

5336

Ceiling Flat  
Latex Acrylic

TECHNICAL DATA SHEET

INTERIOR

## SURFACE PREPARATION

**The surface should be dry and clean**, free from dust, oil, grease, rust and soap. On painted surface, it is recommended to clean with a degreaser (TSP) in order to remove any contaminant that could interfere with the adhesion and/or the full cure of the product. Rinse the entire surface thoroughly. Surfaces must be well sanded and dusted.

**Presence of mold:** Clean the affected area with a mixture of 1 part bleach to 3 parts of water. Rinse before it dries the entire surface thoroughly and let it dry.

**Flaking or peeling:** Using a scraper, remove weakened paint, then sand the edges of the surface to make it smooth.

A repair compound should be used to fill holes and uneven surfaces. Sand with # 150 grit sandpaper.

**New Drywall:** To avoid creating an unwanted texture on the drywall sheet, joint compound should not be sanded excessively.

**Concrete / Masonry:** Allow concrete / masonry to cure at least 30 days before painting.

**Aluminum, galvanized metal, interior ferrous metal:** Remove all traces of oxidation (rust), then clean with Metal Plus 467, Conditioner for metal

**Wood:** The surface should be sanded with # 80 or # 100 grit sandpaper to improve adhesion

## RECOMMENDED PRIMERS

**New Drywall:** Apply Selection 5371

**Concrete/block / rough brick:** Apply Proline 6006 Block Filler to seal and level the texture of the concrete blocks

**Wood without bleeding:** Apply Protico 270

**Wood with bleeding** such as (cedar, redwood, exotic, plywood, recomposed and glued wood and any wood with bleeding): Apply one to two coats of Block Plus 296 alkyd-based.

**WARNING: WOOD IS A NATURAL MATERIAL AND ALTHOUGH IT IS TREATED, BLEEDING MAY RECAP OVER TIME.**

**Pine knots:** Seal pine knots with Stop Plus 298.

**Aluminum, galvanized metal:** Adhero Plus 290

**Interior metal ferrous not rusted:** Adhero Plus 297

**Latex paint high gloss:** Portico 270

**Alkyd paint:** one coat of Adhero Hybrid 297-4

## APPLICATION

This product is ready to use and does not require dilution. Mix well before use. Apply two coats of paint. Allow 4 hours drying time between coats. In order to properly cover the surface, it is recommended to use a 15 mm lint free roller and a quality nylon-polyester brush. Clean rollers and brushes with warm soapy water after using them.

**For spray application:** Maybe diluted with a maximum of 10% water.

**Pressure:** 2000 to 2500 lb/sqin\*

**Nozzle:** 0.015 – 0.019\*

\*This data may vary depending on the brand of the equipment manufacturer

## MAINTENANCE

The paint requires a minimum drying time of 30 days before proceeding with a first cleaning. It is not designed for recurrent cleaning. Use only water, and a soft cloth. Clean the surface with a light and circular movement.

## WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection

## CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

**CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER**